

Wikiprint Book

Title: Documentation/ARexxAPI/ADDRDELETE

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/ADDRDELETE

Version: 8

Date: 30.01.2015 13:26:42

Table of Contents

Languages:	3
ADDRDELETE	3

Languages:

- **English**
- [Español](#)
- [Français](#)

ADDRDELETE

NAME

AddrDelete -- Remove an entry from the address book. (V2.0)

TEMPLATE

ALIAS

FUNCTION

Removes an entry from the address book.

INPUTS

ALIAS - Alias of the entry to be removed. This parameter is optional; if it is missing, AddrDelete will remove the current entry, if any.

RETURNS

RC is set to 5 if ALIAS doesn't exist or if none was provided and there is nothing to delete (because the address book window is closed).

NOTES

If ALIAS refers to a group or distribution list, all their contents are deleted as well.

If the address book window is not opened at the time the command is executed, the deletion cannot be undone. However, the deletion doesn't really affect the address book on disk unless the application is instructed to save the address book with e.g. [ADDRSAVE](#).

EXAMPLE

BUGS

A missing check for a NULL pointer used to make the command cause Enforcer hits if no alias was supplied. This was fixed in V2.4.

SEE ALSO