

Languages:

- English
- Español

ADDREDIT

NAME

AddrEdit — Fill in the fields of the current address book entry.

(V2.0)

TEMPLATE

ALIAS,NAME,EMAIL,PGP,HOMEPAGE,STREET,CITY,COUNTRY,PHONE,COMMENT,
BIRTHDATE/N,IMAGE,MEMBER/M,ADD/S

FUNCTION

Edits the fields of the current address book entry.

INPUTS

ALIAS - alias for the entry (upto 29 chars)
NAME - real name for the entry (upto 39 chars)
EMAIL - email address for the entry
PGP - PGP ID for the entry (person only)
HOMEPAGE - homepage for the entry (person only) (upto 231 chars)
STREET - snail mail address of the entry (person only) (upto 79 chars)
CITY - city for the entry (person only) (upto 79 chars)
COUNTRY - country for the entry (person only) (upto 79 chars)
PHONE - phone # for the entry (person only) (upto 79 chars)
COMMENT - comment for the entry (up to 79 chars)
BIRTHDATE/N - birthdate for a person in DDMMYYYY format, e.g. 13091969
IMAGE - image filename for the entry (person only)
MEMBER/M - use the argument(s) to edit a member list
ADD/S - combined with 'member', adds new members to a distribution list, instead of replacing the old member info


RETURNS

RC is set 10 if no entry is currently selected in the address book.

NOTES

Arguments longer than the available space are simply truncated.

EXAMPLE



BUGS

Even if a group or person is selected, MEMBER [ADD] will return success (0).

Entering nonsense data as birth date or editing a distribution list would throw Enforcer hits; this was fixed in V2.4.

SEE ALSO