

**Languages:**

- **English**
- [Español](#)

**Table of Contents**

Languages:	1
ADDREDIT	2

## ADDREDIT

### NAME

AddrEdit -- Fill in the fields of the current address book entry.

(V2.0)

### TEMPLATE

ALIAS,NAME,EMAIL,PGP,HOMEPAGE,STREET,CITY,COUNTRY,PHONE,COMMENT, BIRTHDATE/N,IMAGE,MEMBER/M,ADD/S

### FUNCTION

Edits the fields of the current address book entry.

### INPUTS

ALIAS - alias for the entry (upto 29 chars)

NAME - real name for the entry (upto 39 chars)

EMAIL - email address for the entry

PGP - PGP ID for the entry (person only)

HOMEPAGE - homepage for the entry (person only) (upto 231 chars)

STREET - snail mail address of the entry (person only) (upto 79 chars)

CITY - city for the entry (person only) (upto 79 chars)

COUNTRY - country for the entry (person only) (upto 79 chars)

PHONE - phone # for the entry (person only) (upto 79 chars)

COMMENT - comment for the entry (up to 79 chars)

BIRTHDATE/N - birthdate for a person in DDMMYYYY format, e.g. 13091969

IMAGE - image filename for the entry (person only)

MEMBER/M - use the argument(s) to edit a member list

ADD/S - combined with 'member', adds new members to a distribution list, instead of replacing the old member info

### RETURNS

RC is set 10 if no entry is currently selected in the address book.

### NOTES

Arguments longer than the available space are simply truncated.

### EXAMPLE

```

/* Enable result codes */
OPTIONS RESULTS

/* Select an entry */
ADDRGOTO YAM_ml

/* Edit this entry */
'ADDREDIT EMAIL "yam@freelists.org" COMMENT "The place to be"

/* Select a distribution list */
ADDRGOTO blacklisted

/* Reset the list */
ADDREDIT MEMBER 'bill'

/* Add a couple of members */
ADDREDIT MEMBER 'jobs@example.com' MEMBER 'smith@example.net' ADD

```

### BUGS

Even if a group or person is selected, MEMBER [ADD] will return success (0).

Entering nonsense data as birth date or editing a distribution list would throw Enforcer hits; this was fixed in V2.4.

**SEE ALSO**