

Error: Macro TranslatedPages(None) failed

expected string or buffer

ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

49. READCLOSE
50. READINFO
51. READPRINT
52. READSAVE
53. REQUEST
54. REQUESTFILE
55. REQUESTFOLDER
56. REQUESTSTRING
57. RESTART
58. SCREENTOBACK
59. SCREENTOFRONT
60. SETFLAG
61. SETFOLDER
62. SETMAIL
63. SETMAILFILE
64. SHOW
65. USERINFO
66. WRITEATTACH
67. WRITEBCC
68. WRITECC
69. WRITEEDITOR
70. WRITEFROM
71. WRITEIDENTITY
72. WRITELETTER
73. WRITEMAILTO
74. WRITEOPTIONS
75. WRITEQUEUE
76. WRITEREPLYTO
77. WRITESEND
78. WRITESUBJECT
79. WRITETO

ADDREDIT

NAME

AddrEdit -- Fill in the fields of the current address book entry. (V2.0)

TEMPLATE

ALIAS,NAME,EMAIL,PGP,HOMEPAGE,STREET,CITY,COUNTRY,PHONE,COMMENT,
BIRTHDATE/N,IMAGE,MEMBER/M,ADD/S

FUNCTION

Edits the fields of the current address book entry.

INPUTS

ALIAS - alias for the entry (upto 29 chars)
 NAME - real name for the entry (upto 39 chars)
 EMAIL - email address for the entry
 PGP - PGP ID for the entry (person only)
 HOMEPAGE - homepage for the entry (person only) (upto 231 chars)
 STREET - snail mail address of the entry (person only) (upto 79 chars)
 CITY - city for the entry (person only) (upto 79 chars)
 COUNTRY - country for the entry (person only) (upto 79 chars)

PHONE - phone # for the entry (person only) (upto 79 chars)
COMMENT - comment for the entry (up to 79 chars)
BIRTHDATE/N - birthdate for a person in DDMMYYYY format, e.g. 13091969
IMAGE - image filename for the entry (person only)
MEMBER/M - use the argument(s) to edit a member list
ADD/S - combined with 'member', adds new members to a distribution list, instead of replacing the old member info

RETURNS

RC is set 10 if no entry is currently selected in the address book.

NOTES

Arguments longer than the available space are simply truncated.

EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Select an entry */
ADDRGOTO YAM_ml

/* Edit this entry */
'ADDREDIT EMAIL "yam@freelists.org" COMMENT "The place to be"'

/* Select a distribution list */
ADDRGOTO blacklisted

/* Reset the list */
ADDREDIT MEMBER 'bill'

/* Add a couple of members */
ADDREDIT MEMBER 'jobs@example.com' MEMBER 'smith@example.net' ADD
```

BUGS

Even if a group or person is selected, MEMBER [ADD] will return success (0).

Entering nonsense data as birth date or editing a distribution list would throw Enforcer hits; this was fixed in V2.4.

SEE ALSO