

## Languages:

- English
- Español

# ADDRFIND

## NAME

AddrFind — Find one or more entries in the address book. (V2.0)

## TEMPLATE

VAR/K,STEM/K,PATTERN/A,NAMEONLY/S,EMAILONLY/S

## FUNCTION

Finds one or more entries in the address book, searching by default in the "Alias", "Real name", "E-mail address", "Description", "Street", "City" and "Country" fields.

## INPUTS

VAR/K- variable to store the results of the query

STEM/K- base name used for the stems where the aliases for the address book entries matching the query will be stored

PATTERN/A - pattern used as search criterion; all the AmigaDOS wildcard characters are supported

NAMEONLY/S- restrict the search to the "Real name" field of the entries in the address book

EMAILONLY/S- restrict the search to the "E-mail address" field of the entries in the address book

## RETURNS

VAR - string containing the number of entries matching the query and a space separated list of the matching aliases.

<stem>ALIAS.COUNT - number of matches found


<stem>ALIAS.NR- the nth alias in the list of aliases matching the query, nr being a number between 0 and n-1.

RC is set to 5 if no match is found.

## NOTES

Aliases are returned in the order they appear in the address book.

## EXAMPLE



BUGS

AddrFind can't search into the "Alias" or "Description" fields of groups.

SEE ALSO

ADDRRESOLVE