

## Error: Macro TranslatedPages(None) failed

expected string or buffer

### ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

49. READCLOSE
50. READINFO
51. READPRINT
52. READSAVE
53. REQUEST
54. REQUESTFILE
55. REQUESTFOLDER
56. REQUESTSTRING
57. RESTART
58. SCREENTOBACK
59. SCREENTOFRONT
60. SETFLAG
61. SETFOLDER
62. SETMAIL
63. SETMAILFILE
64. SHOW
65. USERINFO
66. WRITEATTACH
67. WRITEBCC
68. WRITECC
69. WRITEEDITOR
70. WRITEFROM
71. WRITEIDENTITY
72. WRITELETTER
73. WRITEMAILTO
74. WRITEOPTIONS
75. WRITEQUEUE
76. WRITEREPLYTO
77. WRITESEND
78. WRITESUBJECT
79. WRITETO

## **ADDRFIND**

### NAME

AddrFind -- Find one or more entries in the address book. (V2.0)

### TEMPLATE

VAR/K,STEM/K,PATTERN/A,NAMEONLY/S,EMAILONLY/S

### FUNCTION

Finds one or more entries in the address book, searching by default in the "Alias", "Real name", "E-mail address", "Description", "Street", "City" and "Country" fields.

### INPUTS

VAR/K- variable to store the results of the query  
 STEM/K- base name used for the stems where the aliases for the address book entries matching the query will be stored  
 PATTERN/A - pattern used as search criterion; all the AmigaDOS wildcard characters are supported  
 NAMEONLY/S- restrict the search to the "Real name" field of the entries in the address book  
 EMAILONLY/S- restrict the search to the "E-mail address" field of the entries in the address book

### RETURNS

### ADDRFIND

VAR - string containing the number of entries matching the query and a space separated list of the matching aliases.

<stem>ALIAS.COUNT - number of matches found

<stem>ALIAS.NR- the nth alias in the list of aliases matching the query, nr being a number between 0 and n-1.

RC is set to 5 if no match is found.

## NOTES

Aliases are returned in the order they appear in the address book.

## EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Find all the entries using a given provider */
ADDRFIND PATTERN '#?@saug.org' STEM st. EMAILONLY

/* List results */
IF RC = 0 THEN
  DO i = 0 TO st.alias.count-1
    SAY 'Match #'i+1': 'st.alias.i
  END
ELSE
  SAY 'No matches found.'
EXIT
```

## BUGS

AddrFind can't search into the "Alias" or "Description" fields of groups.

## SEE ALSO

ADDRRESOLVE?