Error: Macro TranslatedPages(None) failed

```
expected string or buffer
```

ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

49. READCLOSE
50. READINFO
51. READPRINT
52. READSAVE
53. REQUEST
54. REQUESTFILE
55. REQUESTFOLDER
56. REQUESTSTRING
57. RESTART
58. SCREENTOBACK
59. SCREENTOFRONT
60. SETFLAG
61. SETFOLDER
62. SETMAIL
63. SETMAILFILE
64. SHOW
65. USERINFO
66. WRITEATTACH
67. WRITEBCC
68. WRITECC
69. WRITEEDITOR
70. WRITEFROM
71. WRITEIDENTITY
72. WRITELETTER
73. WRITEMAILTO
74. WRITEOPTIONS
75. WRITEQUEUE
76. WRITEREPLYTO
77. WRITESEND
78. WRITESUBJECT
79. WRITETO

ADDRLOAD

NAME

AddrLoad -- Load an address book from disk. (V2.0)

TEMPLATE

FILENAME/A,OPEN/S

FUNCTION

Loads the specified address book from disk, replacing the current address book in RAM.

INPUTS

`FILENAME/A` - address book to be loaded
`OPEN/S` - immediately open the address book window after the address book file has been loaded successfully (V2.8p1)

RETURNS

`RC` is set to 10 if the filename cannot be opened.

As of V2.4, this condition also triggers an error requester.

NOTES

Loading a new address book from disk does not count as a change in the address book itself, which means you won't be warned if you try to quit YAM after loading that file, and thus will lose the new information if you forget to save it.

As of V2.4, YAM pays attention to the contents of the supplied file. If the file is not recognised as a valid address book, a requester will open to let the user select whether he wants it to be loaded as a list of email addresses where items can be specified as

```
<email@example.com> Real name
```

or

```
email@example.com
```

because names are optional. YAM will automatically create aliases for the new items, and the command will not return until the requester is satisfied.

EXAMPLE

```
/* Load an address book from disk */
ADDRLOAD 'mail:addresslist'
```

BUGS

SEE ALSO