

Wikiprint Book

Title: Documentation/ARexxAPI/ADDRRESOLVE

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/ADDRRESOLVE

Version: 5

Date: 29.01.2015 05:19:17

Table of Contents

Languages:	3
ADDRRESOLVE	3

Languages:

- **English**
- [Español](#)

ADDRRESOLVE

NAME

AddrResolve -- Resolve an alias or name into the corresponding email address(es). (V2.0)

TEMPLATE

VAR/K,STEM/K,ALIAS/A

FUNCTION

Tries to resolve a given alias or name into the corresponding email address(es). The command can resolve both individuals and distribution lists.

INPUTS

VAR/K - variable where the name and/or address(es) of the resulting recipient(s) will be stored

STEM/K - base name used for the stem where the name and/or address(s) of the resulting recipient(s) will be stored

ALIAS/A - alias or name to be resolved

RETURNS

VAR - name and/or address(es) of the matching entry

<STEM>RECEPT - name and/or address(es) of the matching entry

RC is set to 5 if the supplied alias or name cannot be resolved.

NOTES

EXAMPLE

BUGS

AddrResolve used to crash in a rather spectacular fashion if it couldn't resolve the supplied alias or name. This was fixed in V2.4.

SEE ALSO

[ADDRFIND](#)