

Wikiprint Book

Title: Documentation/ARexxAPI/FOLDERINFO

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/FOLDERINFO

Version: 7

Date: 06/03/15 22:45:08

Table of Contents

Languages:	3
FOLDERINFO	3

Languages:

- **English**
- [Español](#)

FOLDERINFO**NAME**

FolderInfo -- Return information about a folder. (V2.0)

TEMPLATE

VAR/K,STEM/K,FOLDER

FUNCTION

Returns information about the specified folder, or the current folder if none is specified.

INPUTS

VAR/K - variable where the results will be stored

STEM/K - base name used for the stems where the returned data will be stored

FOLDER - name or path of the folder we want to get info about; if no folder is specified, the current folder will be used (V2.2)

RETURNS

VAR - string with a space separated list of the results of the query

<STEM>NUMBER - position of the folder in the folder list; the folder at the top is in slot 0

<STEM>NAME - name of the folder as shown in the folder list

<STEM>PATH - path of the folder, e.g. "incoming"

<STEM>TOTAL - total number of messages in the folder

<STEM>NEW - number of new messages in the folder

<STEM>UNREAD - number of unread messages in the folder

<STEM>SIZE - size of the folder, in bytes

<STEM>TYPE - type of folder (V2.3), possible values are:

0 - normal

1 - incoming

2 - outgoing

3 - sent (for the default "Sent" folder)

4 - deleted

5 - sent and received

6 - sent

RC is set to 10 if the specified folder cannot be found.

NOTES**EXAMPLE**

/* Enable result codes */

OPTIONS RESULTS

/* Request info */

FOLDERINFO 'Incoming' STEM fi.

/* Display results */

SAY 'Folder number: 'fi.number
SAY 'Folder name: 'fi.name
SAY 'Path: 'fi.path
SAY 'Total messages: 'fi.total
SAY 'New messages: 'fi.new
SAY 'Unread messages: 'fi.unread
SAY 'Total size: 'fi.size
SAY 'Type: 'fi.type

BUGS

SEE ALSO