Wikiprint Book

Title: Documentation/ARexxAPI/FOLDERINFO

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/FOLDERINFO

Version: 7

Date: 16.09.2014 17:37:28

Table of Contents

Languages: 3
FOLDERINFO 3

Languages:

- **English**
- Español

FOLDERINFO

NAME

FolderInfo -- Return information about a folder. (V2.0)

TEMPLATE

VAR/K,STEM/K,FOLDER

FUNCTION

Returns information about the specified folder, or the current folder if none is specified.

INPUTS

`VAR/K` - variable where the results will be stored
`STEM/K` - base name used for the stems where the returned data will be stored
`FOLDER` - name or path of the folder we want to get info about; if no folder is specified, the current folder will be used (V2.2)

RETURNS

`VAR` - string with a space separated list of the results of the query
`<STEM>NUMBER` - position of the folder in the folder list; the folder at the top is in slot 0
`<STEM>NAME` - name of the folder as shown in the folder list
`<STEM>PAT` - path of the folder, e.g. "incoming"
`<STEM>TOTAL` - total number of messages in the folder
`<STEM>NEW` - number of new messages in the folder
`<STEM>UNREAD` - number of unread messages in the folder
`<STEM>SIZE` - size of the folder, in bytes
`<STEM>TYPE` - type of folder (V2.3), possible values are:

0 - normal
1 - incoming
2 - outgoing
3 - sent (for the default "Sent" folder)
4 - deleted
5 - sent and received
6 - sent

`RC` is set to 10 if the specified folder cannot be found.

NOTES

EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Request info */
FOLDERINFO 'Incoming' STEM fi.

/* Display results */
SAY 'Folder number:   'fi.number
SAY 'Folder name:     'fi.name
SAY 'Path:            'fi.path
SAY 'Total messages:  'fi.total
SAY 'New messages:    'fi.new
SAY 'Unread messages: 'fi.unread
SAY 'Total size:      'fi.size
SAY 'Type:            'fi.type
```

BUGS

SEE ALSO