

Wikiprint Book

Title: Documentation/ARexxAPI/GETCONFIGINFO

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/GETCONFIGINFO

Version: 11

Date: 30.01.2015 18:06:10

Table of Contents

Languages:	3
GETCONFIGINFO	3

Languages:

- **English**
- [Español](#)

GETCONFIGINFO**NAME**

GetConfigInfo -- Return information about the current user. (V1.3)

TEMPLATE

VAR/K,STEM/K,ITEM/A

FUNCTION

Returns information about the current user.

INPUTS

VAR/K - alternative variable to put the results into instead of RESULT (V2.0)

STEM/K - base name used for the stem where the result will be stored (V2.0)

ITEM/A - item to return information about, may be one of

- EMA(IL) - e-mail address
- NAM(E) - real name

RETURNS

VAR - info returned by the query

<STEM>VALUE - info returned by the query

NOTES

Superseded by [USERINFO](#) in V2.0+. Don't use it in new scripts.

EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Request 'name' info */
GETCONFIGINFO NAME VAR name
IF RC ~= 0 THEN EXIT

/* Request 'email' info */
GETCONFIGINFO EMAIL VAR email
IF RC ~= 0 THEN EXIT

/* Display results */
SAY 'User name:      'name
SAY 'User address: 'email
```

BUGS

The original V1.3 implementation would return junk most of the time; this was fixed in V1.3.1.

SEE ALSO

[USERINFO](#)