Error: Macro TranslatedPages(None) failed

```
expected string or buffer
```

ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

49. READCLOSE
50. READINFO
51. READPRINT
52. READSAVE
53. REQUEST
54. REQUESTFILE
55. REQUESTFOLDER
56. REQUESTSTRING
57. RESTART
58. SCREENTOBACK
59. SCREENTOFRONT
60. SETFLAG
61. SETFOLDER
62. SETMAIL
63. SETMAILFILE
64. SHOW
65. USERINFO
66. WRITEATTACH
67. WRITEBCC
68. WRITECC
69. WRITEEDITOR
70. WRITEFROM
71. WRITEIDENTITY
72. WRITELETTER
73. WRITEMAILTO
74. WRITEOPTIONS
75. WRITEQUEUE
76. WRITEREPLYTO
77. WRITESEND
78. WRITESUBJECT
79. WRITETO

GETFOLDERINFO

NAME

GetFolderInfo -- Return information about the current folder.

TEMPLATE

VAR/K,STEM/K,ITEM/A

FUNCTION

Returns information about the current folder.

INPUTS

`VAR/K` - alternative variable to put the results into instead of RESULT (V2.0)
`STEM/K` - base name used for the stems where the returned data will be stored (V2.0)
`ITEM/A` - item to return info about, may be one of

- ◊ `NUM(BER)` - position in the folder list (0 = first folder)
- ◊ `NAM(E)` - name of the folder as shown in the folder list
- ◊ `MAX` - total number of messages in the folder
- ◊ `PAT(H)` - folder directory, without path (V1.3)

RETURNS

VAR - info returned by the query
<STEM>VALUE - info returned by the query

NOTES

Superseded by FOLDERINFO? in V2.0+. Don't use it in new scripts.

EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Request 'position' info */
GETFOLDERINFO NUMBER VAR position
IF RC ~= 0 THEN EXIT

/* Request 'name' info */
GETFOLDERINFO NAME VAR name
IF RC ~= 0 THEN EXIT

/* Request 'max' info */
GETFOLDERINFO MAX VAR total
IF RC ~= 0 THEN EXIT

/* Request 'path' info */
GETFOLDERINFO PATH VAR path
IF RC ~= 0 THEN EXIT

/* Display results */
SAY 'Folder name:    'name
SAY 'Path:           'path
SAY 'Place in list:  'position
SAY 'Total messages: 'total
```

BUGS

SEE ALSO

FOLDERINFO?