Wikiprint Book

Title: Documentation/ARexxAPI/GETFOLDERINFO

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/GETFOLDERINFO

Version: 8

Date: 06/05/15 06:28:08

Table of Contents

Languages: 3
GETFOLDERINFO 3

Languages:

- **English**
- Español

GETFOLDERINFO

NAME

GetFolderInfo -- Return information about the current folder.

TEMPLATE

VAR/K,STEM/K,ITEM/A

FUNCTION

Returns information about the current folder.

INPUTS

`VAR/K` - alternative variable to put the results into instead of RESULT (V2.0)
`STEM/K` - base name used for the stems where the returned data will be stored (V2.0)
`ITEM/A` - item to return info about, may be one of

- `NUM(BER)` - position in the folder list (0 = first folder)
- `NAM(E)` - name of the folder as shown in the folder list
- `MAX` - total number of messages in the folder
- `PAT(H)` - folder directory, without path (V1.3)

RETURNS

`VAR` - info returned by the query
`<STEM>VALUE` - info returned by the query

NOTES

Superseded by FOLDERINFO in V2.0+. Don't use it in new scripts.

EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Request 'position' info */
GETFOLDERINFO NUMBER VAR position
IF RC ~= 0 THEN EXIT

/* Request 'name' info */
GETFOLDERINFO NAME VAR name
IF RC ~= 0 THEN EXIT

/* Request 'max' info */
GETFOLDERINFO MAX VAR total
IF RC ~= 0 THEN EXIT

/* Request 'path' info */
GETFOLDERINFO PATH VAR path
IF RC ~= 0 THEN EXIT

/* Display results */
SAY 'Folder name:    'name
SAY 'Path:           'path
SAY 'Place in list:  'position
SAY 'Total messages: 'total
```

BUGS

SEE ALSO

FOLDERINFO