

Wikiprint Book

Title: Documentation/ARexxAPI/GETFOLDERINFO

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/GETFOLDERINFO

Version: 8

Date: 27/02/15 08:38:57

Table of Contents

| | |
|---------------|---|
| Languages: | 3 |
| GETFOLDERINFO | 3 |

Languages:

- **English**
- [Español](#)

GETFOLDERINFO**NAME**

GetFolderInfo -- Return information about the current folder.

TEMPLATE

VAR/K,STEM/K,ITEM/A

FUNCTION

Returns information about the current folder.

INPUTS

VAR/K - alternative variable to put the results into instead of RESULT (V2.0)
 STEM/K - base name used for the stems where the returned data will be stored (V2.0)
 ITEM/A - item to return info about, may be one of

NUM(BER) - position in the folder list (0 = first folder)
 NAM(E) - name of the folder as shown in the folder list
 MAX - total number of messages in the folder
 PAT(H) - folder directory, without path (V1.3)

RETURNS

VAR - info returned by the query
 <STEM>VALUE - info returned by the query

NOTES

Superseded by [FOLDERINFO ?](#) in V2.0+. Don't use it in new scripts.

EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Request info */

GETFOLDERINFO NUMBER VAR position
GETFOLDERINFO NAME VAR name
GETFOLDERINFO MAX VAR total
GETFOLDERINFO PATH VAR path

/* Display results */

SAY 'Folder name: 'name
SAY 'Path: 'path
SAY 'Place in list: 'position
SAY 'Total messages: 'total
```

BUGS**SEE ALSO**

[FOLDERINFO ?](#)