

Languages:

- **English**
- [Español](#)

Table of Contents

Languages:	1
GETFOLDERINFO	2

GETFOLDERINFO

NAME

GetFolderInfo -- Return information about the current folder.

TEMPLATE

VAR/K,STEM/K,ITEM/A

FUNCTION

Returns information about the current folder.

INPUTS

VAR/K - alternative variable to put the results into instead of RESULT (V2.0)
STEM/K - base name used for the stems where the returned data will be stored (V2.0)
ITEM/A - item to return info about, may be one of

NUM(BER) - position in the folder list (0 = first folder)
NAM(E) - name of the folder as shown in the folder list
MAX - total number of messages in the folder
PAT(H) - folder directory, without path (V1.3)

RETURNS

VAR - info returned by the query
<STEM>VALUE - info returned by the query

NOTES

Superseded by [FOLDERINFO ?](#) in V2.0+. Don't use it in new scripts.

EXAMPLE

```
/* Enable result codes */
```

```
OPTIONS RESULTS
```

```
/* Request info */
```

```
GETFOLDERINFO NUMBER VAR position  
GETFOLDERINFO NAME VAR name  
GETFOLDERINFO MAX VAR total  
GETFOLDERINFO PATH VAR path
```

```
/* Display results */
```

```
SAY 'Folder name: 'name  
SAY 'Path: 'path  
SAY 'Place in list: 'position  
SAY 'Total messages: 'total
```

BUGS

SEE ALSO

[FOLDERINFO ?](#)