

## **Wikiprint Book**

**Title: Documentation/ARexxAPI/GETFOLDERINFO**

**Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/GETFOLDERINFO**

**Version: 8**

**Date: 30.01.2015 03:41:40**

## Table of Contents

Languages:	3
GETFOLDERINFO	3

**Languages:**

- **English**
- [Español](#)

**GETFOLDERINFO****NAME**

GetFolderInfo -- Return information about the current folder.

**TEMPLATE**

VAR/K,STEM/K,ITEM/A

**FUNCTION**

Returns information about the current folder.

**INPUTS**

VAR/K - alternative variable to put the results into instead of RESULT (V2.0)  
 STEM/K - base name used for the stems where the returned data will be stored (V2.0)  
 ITEM/A - item to return info about, may be one of

NUM(BER) - position in the folder list (0 = first folder)  
 NAM(E) - name of the folder as shown in the folder list  
 MAX - total number of messages in the folder  
 PAT(H) - folder directory, without path (V1.3)

**RETURNS**

VAR - info returned by the query  
 <STEM>VALUE - info returned by the query

**NOTES**

Superseded by [FOLDERINFO ?](#) in V2.0+. Don't use it in new scripts.

**EXAMPLE**

*/\* Enable result codes \*/*

OPTIONS RESULTS

*/\* Request info \*/*

GETFOLDERINFO NUMBER VAR position  
 GETFOLDERINFO NAME VAR name  
 GETFOLDERINFO MAX VAR total  
 GETFOLDERINFO PATH VAR path

*/\* Display results \*/*

SAY 'Folder name: 'name  
 SAY 'Path: 'path  
 SAY 'Place in list: 'position  
 SAY 'Total messages: 'total

**BUGS****SEE ALSO**

[FOLDERINFO ?](#)