

**Languages:**

- English
- [Español](#)

**Table of Contents**

Languages:	1
GETFOLDERINFO	2

## GETFOLDERINFO

### NAME

GetFolderInfo -- Return information about the current folder.

### TEMPLATE

VAR/K,STEM/K,ITEM/A

### FUNCTION

Returns information about the current folder.

### INPUTS

VAR/K - alternative variable to put the results into instead of RESULT (V2.0)

STEM/K - base name used for the stems where the returned data will be stored (V2.0)

ITEM/A - item to return info about, may be one of

- NUM(BER) - position in the folder list (0 = first folder)
- NAM(E) - name of the folder as shown in the folder list
- MAX - total number of messages in the folder
- PAT(H) - folder directory, without path (V1.3)

### RETURNS

VAR - info returned by the query

<STEM>VALUE - info returned by the query

### NOTES

Superseded by [FOLDERINFO](#) in V2.0+. Don't use it in new scripts.

### EXAMPLE

```

/* Enable result codes */
OPTIONS RESULTS

/* Request 'position' info */
GETFOLDERINFO NUMBER VAR position

/* Only continue if RC == 0 */
IF RC ~= 0 THEN EXIT

/* Request 'name' info */
GETFOLDERINFO NAME VAR name

/* Only continue if RC == 0 */
IF RC ~= 0 THEN EXIT

/* Request 'max' info */
GETFOLDERINFO MAX VAR total

/* Only continue if RC == 0 */
IF RC ~= 0 THEN EXIT

/* Request 'path' info */
GETFOLDERINFO PATH VAR path

/* Only continue if RC == 0 */
IF RC ~= 0 THEN EXIT

/* Display results */
SAY 'Folder name:      'name
SAY 'Path:            'path
SAY 'Place in list:   'position
SAY 'Total messages: 'total

```

### BUGS

### SEE ALSO

[FOLDERINFO](#)