Wikiprint Book

Title: Documentation/ARexxAPI/GETMAILINFO

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/GETMAILINFO

Version: 6

Date: 12/02/2015 12:48:11 AM

Table of Contents

Languages: 3
GETMAILINFO 3

Languages:

- **English**
- Español

GETMAILINFO

NAME

GetMailInfo -- Return information about the current message.

TEMPLATE

VAR/K,STEM/K,ITEM/A

FUNCTION

Returns information about the current message.

INPUTS

`VAR/K` - alternative variable to put the results into instead of RESULT (V2.0)
`STEM/K`- base name used for the stems where the returned data will be stored (V2.0)
`ITEM/A` - item to return info about, may be one of

- `ACT(IVE)` - position (0 = first message in the folder)
  `STA(TUS)` - status of the message, possible values are
  - `N` - new
  - `O` - read
  - `U` - unread
  - `R` - replied
  - `F` - forwarded
  - `S` - sent
  - `W` - pending
  - `H` - hold
  - `E` - error sending
- `FRO(M)` - sender
- `TO` - primary recipient
- `REP(LY)` - return address; this will be either the first recipient in the "Reply-To:" header, or the first sender in the "From:" header if no "Reply-To:" header exists
- `SUB(JECT)` - subject
- `FIL(E)` - full path of the message file

RETURNS

`VAR` - info returned by the query
`<STEM>VALUE` - info returned by the query

NOTES

Superseded by MAILINFO in V2.0+. Don't use it in new scripts.

EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Request 'active' info */
GETMAILINFO ACTIVE VAR posi
IF RC ~= 0 THEN EXIT

/* Request 'status' info */
GETMAILINFO STATUS VAR status
IF RC ~= 0 THEN EXIT

/* Request 'from' info */
GETMAILINFO FROM VAR from
IF RC ~= 0 THEN EXIT
```

```
/* Request 'to' info */
GETMAILINFO TO VAR to
IF RC ~= 0 THEN EXIT

/* Request 'reply' info */
GETMAILINFO REPLY VAR replyto
IF RC ~= 0 THEN EXIT

/* Request 'subject' info */
GETMAILINFO SUBJECT VAR subj
IF RC ~= 0 THEN EXIT

/* Request 'file' info */
GETMAILINFO FILE VAR path
IF RC ~= 0 THEN EXIT

/* Display results */
SAY 'Position: 'posi
SAY 'Status:   'status
SAY 'From:     'from
SAY 'To:       'to
SAY 'Reply-To: 'replyto
SAY 'Subject:  'subj
SAY 'Path:     'path
```

BUGS

SEE ALSO

MAILINFO