Wikiprint Book

Title: Documentation/ARexxAPI/GETMAILINFO

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/GETMAILINFO

Version: 6

Date: 03/09/15 11:00:06

Table of Contents

GETMAILINFO 3

GETMAILINFO

NAME

GetMailInfo -- Return information about the current message.

TEMPLATE

VAR/K,STEM/K,ITEM/A

FUNCTION

Returns information about the current message.

INPUTS

VAR/K - alternative variable to put the results into instead of RESULT (V2.0)
STEM/K - base name used for the stems where the returned data will be stored (V2.0)
ITEM/A - item to return info about, may be one of

ACT(IVE) - position (0 = first message in the folder)
STA(TUS) - status of the message, possible values are

N - new
O - read
U - unread
R - replied
F - forwarded
S - sent
W - pending
H - hold
E - error sending

FRO(M) - sender
TO - primary recipient
REP(LY) - return address; this will be either the first recipient in the "Reply-To:" header, or the first sender in the "From:" header if no "Reply-To:" header exists
SUB(JECT) - subject
FIL(E) - full path of the message file

RETURNS

VAR - info returned by the query
<STEM>VALUE - info returned by the query

NOTES

Superseded by MAILINFO ? in V2.0+. Don't use it in new scripts.

EXAMPLE

```
/* Enable result codes */

OPTIONS RESULTS

/* Request info */

GETMAILINFO ACTIVE VAR posi
GETMAILINFO STATUS VAR status
GETMAILINFO FROM VAR from
GETMAILINFO TO VAR to
GETMAILINFO REPLY VAR replyto
GETMAILINFO SUBJECT VAR subj
GETMAILINFO FILE VAR path
```

```
/* Display results */

SAY 'Position: 'posi
SAY 'Status: 'status
SAY 'From: 'from
SAY 'To: 'to
SAY 'Reply-To: 'replyto
SAY 'Subject: 'subj
SAY 'Path: 'path
```

BUGS

SEE ALSO

MAILINFO ?