

## **Wikiprint Book**

**Title: Documentation/ARexxAPI/GETMAILINFO**

**Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/GETMAILINFO**

**Version: 6**

**Date: 01.02.2015 23:42:07**

## Table of Contents

Languages:	3
GETMAILINFO	3

**Languages:**

- English
- [Español](#)

**GETMAILINFO****NAME**

GetMailInfo -- Return information about the current message.

**TEMPLATE**

VAR/K,STEM/K,ITEM/A

**FUNCTION**

Returns information about the current message.

**INPUTS**

VAR/K - alternative variable to put the results into instead of RESULT (V2.0)  
 STEM/K - base name used for the stems where the returned data will be stored (V2.0)  
 ITEM/A - item to return info about, may be one of

ACT(IVE) - position (0 = first message in the folder)  
 STA(TUS) - status of the message, possible values are

N - new  
 O - read  
 U - unread  
 R - replied  
 F - forwarded  
 S - sent  
 W - pending  
 H - hold  
 E - error sending

FRO(M) - sender  
 TO - primary recipient  
 REP(LY) - return address; this will be either the first recipient in the "Reply-To:" header, or the first sender in the "From:" header if no "Reply-To:" header exists  
 SUB(JECT) - subject  
 FIL(E) - full path of the message file

**RETURNS**

VAR - info returned by the query  
 <STEM>VALUE - info returned by the query

**NOTES**

Superseded by [MAILINFO ?](#) in V2.0+. Don't use it in new scripts.

**EXAMPLE**

/\* Enable result codes \*/

OPTIONS RESULTS

/\* Request info \*/

GETMAILINFO ACTIVE VAR posi  
 GETMAILINFO STATUS VAR status

```
GETMAILINFO FROM VAR from  
GETMAILINFO TO VAR to  
GETMAILINFO REPLY VAR replyto  
GETMAILINFO SUBJECT VAR subj  
GETMAILINFO FILE VAR path
```

```
/* Display results */
```

```
SAY 'Position: 'posi  
SAY 'Status: 'status  
SAY 'From: 'from  
SAY 'To: 'to  
SAY 'Reply-To: 'replyto  
SAY 'Subject: 'subj  
SAY 'Path: 'path
```

## **BUGS**

## **SEE ALSO**

[MAILINFO ?](#)