

Languages:

- **English**
- [Español](#)

Table of Contents

Languages:	1
GETMAILINFO	2

GETMAILINFO**NAME**

GetMailInfo -- Return information about the current message.

TEMPLATE

VAR/K,STEM/K,ITEM/A

FUNCTION

Returns information about the current message.

INPUTS

VAR/K - alternative variable to put the results into instead of RESULT (V2.0)
 STEM/K - base name used for the stems where the returned data will be stored (V2.0)
 ITEM/A - item to return info about, may be one of

ACT(IVE) - position (0 = first message in the folder)
 STA(TUS) - status of the message, possible values are

N - new
 O - read
 U - unread
 R - replied
 F - forwarded
 S - sent
 W - pending
 H - hold
 E - error sending

FRO(M) - sender
 TO - primary recipient
 REP(LY) - return address; this will be either the first recipient in the "Reply-To:" header, or the first sender in the "From:" header if no "Reply-To:" header exists
 SUB(JECT) - subject
 FIL(E) - full path of the message file

RETURNS

VAR - info returned by the query
 <STEM>VALUE - info returned by the query

NOTES

Superseded by [MAILINFO ?](#) in V2.0+. Don't use it in new scripts.

EXAMPLE

/* Enable result codes */

OPTIONS RESULTS

/* Request info */

GETMAILINFO ACTIVE VAR posi
 GETMAILINFO STATUS VAR status
 GETMAILINFO FROM VAR from
 GETMAILINFO TO VAR to
 GETMAILINFO REPLY VAR replyto
 GETMAILINFO SUBJECT VAR subj
 GETMAILINFO FILE VAR path

/* Display results */

SAY 'Position: 'posi

SAY 'Status: 'status

SAY 'From: 'from

SAY 'To: 'to

SAY 'Reply-To: 'replyto

SAY 'Subject: 'subj

SAY 'Path: 'path

BUGS

SEE ALSO

[MAILINFO ?](#)