

Error: Macro TranslatedPages(None) failed

expected string or buffer

ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

49. READCLOSE
50. READINFO
51. READPRINT
52. READSAVE
53. REQUEST
54. REQUESTFILE
55. REQUESTFOLDER
56. REQUESTSTRING
57. RESTART
58. SCREENTOBACK
59. SCREENTOFRONT
60. SETFLAG
61. SETFOLDER
62. SETMAIL
63. SETMAILFILE
64. SHOW
65. USERINFO
66. WRITEATTACH
67. WRITEBCC
68. WRITECC
69. WRITEEDITOR
70. WRITEFROM
71. WRITEIDENTITY
72. WRITELETTER
73. WRITEMAILTO
74. WRITEOPTIONS
75. WRITEQUEUE
76. WRITEREPLYTO
77. WRITESEND
78. WRITESUBJECT
79. WRITETO

GETMAILINFO

NAME

GetMailInfo -- Return information about the current message.

TEMPLATE

VAR/K,STEM/K,ITEM/A

FUNCTION

Returns information about the current message.

INPUTS

VAR/K - alternative variable to put the results into instead of RESULT (V2.0)

STEM/K- base name used for the stems where the returned data will be stored (V2.0)

ITEM/A - item to return info about, may be one of

◊ ACT (IVE) - position (0 = first message in the folder)

◊ STA (TUS) - status of the message, possible values are

· N - new

· O - read

· U - unread

· R - replied

- F - forwarded
- S - sent
- W - pending
- H - hold
- E - error sending
- ◇ FRO (M) - sender
- ◇ TO - primary recipient
- ◇ REP (LY) - return address; this will be either the first recipient in the "Reply-To:" header, or the first sender in the "From:" header if no "Reply-To:" header exists
- ◇ SUB (JECT) - subject
- ◇ FIL (E) - full path of the message file

RETURNS

VAR - info returned by the query
 <STEM>VALUE - info returned by the query

NOTES

Superseded by MAILINFO? in V2.0+. Don't use it in new scripts.

EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Request 'active' info */
GETMAILINFO ACTIVE VAR posi
IF RC ~= 0 THEN EXIT

/* Request 'status' info */
GETMAILINFO STATUS VAR status
IF RC ~= 0 THEN EXIT

/* Request 'from' info */
GETMAILINFO FROM VAR from
IF RC ~= 0 THEN EXIT

/* Request 'to' info */
GETMAILINFO TO VAR to
IF RC ~= 0 THEN EXIT

/* Request 'reply' info */
GETMAILINFO REPLY VAR replyto
IF RC ~= 0 THEN EXIT

/* Request 'subject' info */
GETMAILINFO SUBJECT VAR subj
IF RC ~= 0 THEN EXIT

/* Request 'file' info */
GETMAILINFO FILE VAR path
IF RC ~= 0 THEN EXIT

/* Display results */
SAY 'Position: 'posi
SAY 'Status:   'status
SAY 'From:    'from
SAY 'To:      'to
SAY 'Reply-To: 'replyto
SAY 'Subject: 'subj
SAY 'Path:    'path
```

BUGS

GETMAILINFO

SEE ALSO
MAILINFO?