

Languages:

- English
- [Español](#)

Table of Contents

Languages:	1
GETMAILINFO	2

GETMAILINFO

NAME

GetMailInfo -- Return information about the current message.

TEMPLATE

VAR/K,STEM/K,ITEM/A

FUNCTION

Returns information about the current message.

INPUTS

VAR/K - alternative variable to put the results into instead of RESULT (V2.0)

STEM/K- base name used for the stems where the returned data will be stored (V2.0)

ITEM/A - item to return info about, may be one of

- ACT(IVE) - position (0 = first message in the folder)
- STA(TUS) - status of the message, possible values are
 - N - new
 - O - read
 - U - unread
 - R - replied
 - F - forwarded
 - S - sent
 - W - pending
 - H - hold
 - E - error sending
- FRO(M) - sender
- TO - primary recipient
- REP(LY) - return address; this will be either the first recipient in the "Reply-To:" header, or the first sender in the "From:" header if no "Reply-To:" header exists
- SUB(JECT) - subject
- FIL(E) - full path of the message file

RETURNS

VAR - info returned by the query

<STEM>VALUE - info returned by the query

NOTES

Superseded by [MAILINFO](#) in V2.0+. Don't use it in new scripts.

EXAMPLE

```

/* Enable result codes */
OPTIONS RESULTS

/* Request 'active' info */
GETMAILINFO ACTIVE VAR posi
IF RC ~= 0 THEN EXIT

/* Request 'status' info */
GETMAILINFO STATUS VAR status
IF RC ~= 0 THEN EXIT

/* Request 'from' info */
GETMAILINFO FROM VAR from
IF RC ~= 0 THEN EXIT

/* Request 'to' info */
GETMAILINFO TO VAR to
IF RC ~= 0 THEN EXIT

/* Request 'reply' info */
GETMAILINFO REPLY VAR replyto

```

```
IF RC ~= 0 THEN EXIT

/* Request 'subject' info */
GETMAILINFO SUBJECT VAR subj
IF RC ~= 0 THEN EXIT

/* Request 'file' info */
GETMAILINFO FILE VAR path
IF RC ~= 0 THEN EXIT

/* Display results */
SAY 'Position: 'posi
SAY 'Status: 'status
SAY 'From: 'from
SAY 'To: 'to
SAY 'Reply-To: 'replyto
SAY 'Subject: 'subj
SAY 'Path: 'path
```

BUGS

SEE ALSO

[MAILINFO](#)