

Wikiprint Book

Title: Documentation/ARexxAPI/GETSELECTED

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/GETSELECTED

Version: 6

Date: 01.02.2015 20:48:20

Table of Contents

Languages:	3
GETSELECTED	3

Languages:

- **English**
- [Español](#)

GETSELECTED**NAME**

GetSelected -- Get the position of the messages selected in the current folder. (V2.0)

TEMPLATE

VAR/K,STEM/K

FUNCTION

Gets the position of the messages selected in the current folder.

INPUTS

VAR/K - alternative variable to put the results into instead of RESULT

STEM/K - base name used for the stems where the returned data will be stored

RETURNS

VAR - space separated list of results

<STEM>NUM.COUNT - number of selected messages

<STEM>NUM.NR - position of the nth selected message, starting from 0; the message at the top of the list is also at position 0

The result is just "0" if an empty folder or a folder group are currently selected.

NOTES**EXAMPLE**

```
/* Enable result codes */
OPTIONS RESULTS

/* Request info */
GETSELECTED STEM st.

/* Only continue if RC == 0 */
IF RC ~= 0 THEN EXIT

/* Display results */
SAY 'Messages selected: ' st.num.count
DO i = 0 TO st.num.count-1
  SAY 'Position of msg #' i': ' st.num.i
END
```

BUGS

<STEM>NUM.COUNT was not initialized for empty folders. This was fixed in V2.4.

SEE ALSO