

## **Wikiprint Book**

**Title: Documentation/ARexxAPI/GETSELECTED**

**Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/GETSELECTED**

**Version: 6**

**Date: 27.01.2015 15:31:35**

## Table of Contents

Languages:	3
GETSELECTED	3

**Languages:**

- **English**
- [Español](#)

**GETSELECTED****NAME**

GetSelected -- Get the position of the messages selected in the current folder. (V2.0)

**TEMPLATE**

VAR/K,STEM/K

**FUNCTION**

Gets the position of the messages selected in the current folder.

**INPUTS**

VAR/K - alternative variable to put the results into instead of RESULT  
STEM/K - base name used for the stems where the returned data will be stored

**RETURNS**

VAR - space separated list of results  
<STEM>NUM.COUNT - number of selected messages  
<STEM>NUM.NR - position of the nth selected message, starting from 0; the message at the top of the list is also at position 0

The result is just "0" if an empty folder or a folder group are currently selected.

**NOTES****EXAMPLE**

```
/* Enable result codes */

OPTIONS RESULTS

/* Request info */

GETSELECTED STEM st.

/* Display results */

SAY 'Messages selected: 'st.num.count
DO i = 0 TO st.num.count-1

    SAY 'Position of msg #'i': 'st.num.i

END
```

**BUGS**

<STEM>NUM.COUNT was not initialized for empty folders. This was fixed in V2.4.

**SEE ALSO**