Error: Macro TranslatedPages(None) failed

```
expected string or buffer
```

ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

49. READCLOSE
50. READINFO
51. READPRINT
52. READSAVE
53. REQUEST
54. REQUESTFILE
55. REQUESTFOLDER
56. REQUESTSTRING
57. RESTART
58. SCREENTOBACK
59. SCREENTOFRONT
60. SETFLAG
61. SETFOLDER
62. SETMAIL
63. SETMAILFILE
64. SHOW
65. USERINFO
66. WRITEATTACH
67. WRITEBCC
68. WRITECC
69. WRITEEDITOR
70. WRITEFROM
71. WRITEIDENTITY
72. WRITELETTER
73. WRITEMAILTO
74. WRITEOPTIONS
75. WRITEQUEUE
76. WRITEREPLYTO
77. WRITESEND
78. WRITESUBJECT
79. WRITETO

GETURL

NAME

GetURL -- Download a file from the World Wide Web using HTTP. (V2.1)

TEMPLATE

URL/A,FILENAME/A

FUNCTION

Downloads a file from the World Wide Web by HTTP and saves it to disk.

INPUTS

`URL/A` - complete URL to the file
`FILENAME/A` - complete filename to write the file to

RETURNS

`RC` is set to 5 if a TCP/IP stack is not running, or 10 if it is actually running but not online, if the URL cannot be found, or if the output filename cannot be written to.

NOTES

The "http://" introducer is optional, but otherwise the only one supported.

EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Ignore possible error from GETURL */
OPTIONS FAILAT 11

/* Download a file */
GETURL '!http://yam.ch/files/YAM22.lha' 'ram:YAM22.lha'

/* Report results */
c = RC
SELECT
WHEN c = 5 THEN SAY 'TCP/IP stack not running.'
  WHEN c > 5 THEN SAY 'Error.'
    OTHERWISE SAY 'File downloaded successfully.'
  END
```

BUGS

The command is interrupted if email is sent or received.

SEE ALSO