

Error: Macro TranslatedPages(None) failed

expected string or buffer

ARexx API

MAILEDIT

NAME

MailEdit -- Edit the current message in a new Write window. (V2.0)

TEMPLATE

VAR/K,STEM/K,QUIET/S

FUNCTION

Opens a new Write window to edit the selected message.

INPUTS

VAR/K - alternative variable to store the number of the created window instead of RESULT

STEM/K - base name used for the stem where the returned data will be stored

QUIET/S - force the window to stay invisible (V2.1)

RETURNS

VAR - info returned by the command

<STEM>WINDOW - number of the created window, may be either 0 or 1 (or 2, if QUIET is enabled)

RC is set to 10 if the window cannot be opened, maybe because the limit of two Write windows has been reached.

NOTES

The command works even with email that is NOT intended as "outgoing", like email in the Incoming folder for instance, in which case the [Send now] and [Hold] buttons in the Write window are disabled. After being edited, the mail is marked as "ready to send" no matter in which folder it is located, and all the old headers are replaced except for "From:" and "To:", which must be manually edited. Special care must be taken to ensure that these remain valid in the resulting message and no "undisclosed-recipients;" or some such remains there by the time it is again saved. Handle with caution.

EXAMPLE

```
/* Select the first message in the Outgoing folder */
```

```
SETFOLDER Outgoing  
SETMAIL 0
```

/* Edit this message */

MAILEDIT

/* Change the subject */

'WRITESUBJECT "Email address change"'

/* Put the message again in the queue */

WRITEQUEUE

BUGS

SEE ALSO