

## Error: Macro TranslatedPages(None) failed

expected string or buffer

### ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

49. READCLOSE
50. READINFO
51. READPRINT
52. READSAVE
53. REQUEST
54. REQUESTFILE
55. REQUESTFOLDER
56. REQUESTSTRING
57. RESTART
58. SCREENTOBACK
59. SCREENTOFRONT
60. SETFLAG
61. SETFOLDER
62. SETMAIL
63. SETMAILFILE
64. SHOW
65. USERINFO
66. WRITEATTACH
67. WRITEBCC
68. WRITECC
69. WRITEEDITOR
70. WRITEFROM
71. WRITEIDENTITY
72. WRITELETTER
73. WRITEMAILTO
74. WRITEOPTIONS
75. WRITEQUEUE
76. WRITEREPLYTO
77. WRITESEND
78. WRITESUBJECT
79. WRITETO

## MAILEDIT

### NAME

MailEdit -- Edit the current message in a new Write window. (V2.0)

### TEMPLATE

VAR/K,STEM/K,QUIET/S

### FUNCTION

Opens a new Write window to edit the selected message.

### INPUTS

VAR/K - alternative variable to store the number of the created window instead of RESULT

STEM/K - base name used for the stem where the returned data will be stored

QUIET/S - force the window to stay invisible (V2.1)

### RETURNS

VAR - info returned by the command

<STEM>WINDOW - number of the created window

RC is set to 10 if the window cannot be opened, maybe because the limit of two Write windows has been reached.

## NOTES

The command works even with email that is NOT intended as "outgoing", like email in the Incoming folder for instance, in which case the [Send now] and [Hold] buttons in the Write window are disabled. After being edited, the mail is marked as "ready to send" no matter in which folder it is located, and all the old headers are replaced except for "From:" and "To:", which must be manually edited. Special care must be taken to ensure that these remain valid in the resulting message and no "undisclosed-recipients;" or some such remains there by the time it is again saved. Handle with caution.

## EXAMPLE

```
/* Select the first message in the Outgoing folder */
SETFOLDER Outgoing
SETMAIL 0

/* Edit this message */
MAILEDIT

/* Change the subject */
'WRITESUBJECT "Email address change"'

/* Put the message again in the queue */
WRITEQUEUE
```

## BUGS

## SEE ALSO