

## **Wikiprint Book**

**Title: Documentation/ARexxAPI/MAILFORWARD**

**Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/MAILFORWARD**

**Version: 5**

**Date: 03/03/15 00:21:26**

## Table of Contents

Languages:	3
MAILFORWARD	3

**Languages:**

- **English**
- [Español](#)

**MAILFORWARD**

**NAME**

MailForward -- Open a new Write window to forward the selected messages.

**TEMPLATE**

VAR/K,STEM/K,QUIET/S

**FUNCTION**

Opens a new Write window to forward the selected messages.

**INPUTS**

VAR/K - alternative variable to put the results into instead of RESULT (V2.0)

STEM/K - base name used for the stem where the number of the created window will be stored (V2.0)

QUIET/S - force the window to stay invisible (V2.1)

**RETURNS**

VAR - info returned by the command

<STEM>WINDOW - number of the created window, may be 0 or 1 (or 2, if QUIET is enabled)

RC is set to 10 if the window cannot be opened, maybe because the limit of two Write windows has been reached.

**NOTES**

**EXAMPLE**

```
/* Silently forward the selected messages */
```

```
MAILFORWARD QUIET
```

```
WRITETO 'joe@?'
```

```
WRITESEND
```

**BUGS**

**SEE ALSO**