

Error: Macro TranslatedPages(None) failed

expected string or buffer

ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

- 49. READCLOSE
- 50. READINFO
- 51. READPRINT
- 52. READSAVE
- 53. REQUEST
- 54. REQUESTFILE
- 55. REQUESTFOLDER
- 56. REQUESTSTRING
- 57. RESTART
- 58. SCREENTOBACK
- 59. SCREENTOFRONT
- 60. SETFLAG
- 61. SETFOLDER
- 62. SETMAIL
- 63. SETMAILFILE
- 64. SHOW
- 65. USERINFO
- 66. WRITEATTACH
- 67. WRITEBCC
- 68. WRITECC
- 69. WRITEEDITOR
- 70. WRITEFROM
- 71. WRITEIDENTITY
- 72. WRITELETTER
- 73. WRITEMAILTO
- 74. WRITEOPTIONS
- 75. WRITEQUEUE
- 76. WRITEREPLYTO
- 77. WRITESEND
- 78. WRITESUBJECT
- 79. WRITETO

MAILSTATUS

NAME

MailStatus -- Change the status of the selected messages. (V2.0)

TEMPLATE

STATUS/A

FUNCTION

Changes the status of the selected messages.

Only the basic "read", "unread", "on hold" and "ready to send" status can be changed with the command; additional flags like "marked", "important", etc. remain untouched.

INPUTS

STATUS/A - may be one of:

- ◇ H - on hold
- ◇ N - new and unread
- ◇ O - old and read
- ◇ Q - queued for sending
- ◇ R - the same as O

- ◇ U - old unread
- ◇ W - the same as Q

RETURNS

RC is set to 5 if no valid STATUS is supplied, or to 10 if it is not supplied at all.

NOTES

The command won't mind the type of folder, i.e. it will change the status of a message in the Incoming folder to "Ready to send" if instructed to do so.

EXAMPLE

```
/* Switch all selected messages to "Unread" */  
MAILSTATUS U
```

BUGS

SEE ALSO