

## **Wikiprint Book**

**Title: Documentation/ARexxAPI/NEWMAILFILE**

**Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/NEWMAILFILE**

**Version: 4**

**Date: 30.01.2015 01:25:31**

## Table of Contents

Languages:	3
NEWMAILFILE	3

**Languages:**

- **English**
- [Español](#)

**NEWMAILFILE**

**NAME**

NewMailFile -- Return a valid, but unused message filename for a folder. (V2.0)

**TEMPLATE**

VAR/K,STEM/K,FOLDER

**FUNCTION**

Returns a valid but still unused message filename for a folder, based on the current date. This is the filename that YAM will use when adding the next message to this folder.

**INPUTS**

VAR/K - alternative variable to put the results into instead of RESULT  
STEM/K - base name used for the stem where the filename will be returned  
FOLDER - optional, name or number of the folder; if none is supplied, the current folder will be used

**RETURNS**

VAR - filename returned, with path  
<STEM>FILENAME - filename returned, with path

RC is set to 10 if the specified folder doesn't exist or a group is currently selected.

**NOTES**

The command works by trying to lock the first message slot usable for the current date (e.g. Work:YAM/folder\_name/09097.001 for Nov 28, 2002) and then working from there until the lock fails.

**EXAMPLE**

**BUGS**

**SEE ALSO**