

Wikiprint Book

Title: Documentation/ARexxAPI/READINFO

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/READINFO

Version: 6

Date: 29.01.2015 17:21:49

Table of Contents

| | |
|------------|---|
| Languages: | 3 |
| READINFO | 3 |

Languages:

- English
- [Español](#)

READINFO**NAME**

ReadInfo -- Return information about the attachments of the message in the active Read window. (V2.0)

TEMPLATE

VAR/K,STEM/K

FUNCTION

Returns information about the attachments of the message in the active Read window as set by [MAILREAD ?](#).

INPUTS

VAR/K - alternative variable to put the results into instead of RESULT
STEM/K - base name used for the stems where the results will be stored

RETURNS

VAR - info returned by the query
<STEM>FILENAME.COUNT - number of parts of the message, excluding the first header block
<STEM>FILENAME.NR - filename of the nth part of the message, where nr is a number between 0 and n-1 (0 = first part after the headers, usually the body of the message)
<STEM>FILETYPE.NR - content type of the nth part of the message, where nr is a number between 0 and n-1 (0 = first part after the headers, usually the body of the message)
<STEM>FILESIZE.NR - size of the nth part of the message, where nr is a number between 0 and n-1 (0 = first part after the headers, usually the body of the message)
<STEM>TEMPFILE.NR - temporary file where the nth part of the message is stored, nr being a number between 0 and n-1 (0 = first part after the headers, usually the body of the message)

RC is set to 10 if no Read window was previously specified as "active" with [MAILREAD ?](#).

NOTES

No filename is returned for the body of the message.

EXAMPLE

```
/* Enable result codes */
```

```
OPTIONS RESULTS
```

```
/* Silently decode the current message */
```

```
MAILREAD QUIET
```

```
/* Get info about the message, then close the window */
```

```
READINFO STEM ri.
```

```
READCLOSE
```

```
/* Display results */
```

```
DO i = 0 TO ri.filename.count-1
```

```
  SAY 'Information about part #i+1
```

```
  SAY ' File name: 'ri.filename.i
```

```
  SAY ' File type: 'ri.filetype.i
```

```
SAY ' File size: 'ri.filesize.i  
SAY ' Stored in: 'ri.tempfile.i
```

END

BUGS

The command used to blindly act upon the first Read window opened at any given time; this was changed in V2.4 to require the use of [MAILREAD ?](#) to explicitly mark a window as "active".

SEE ALSO

[MAILREAD ?](#)