

## **Wikiprint Book**

**Title: Documentation/ARexxAPI/READINFO**

**Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/READINFO**

**Version: 6**

**Date: 09/25/2016 09:06:33 AM**

**Table of Contents**

Languages:	3
READINFO	3

**Languages:**

- **English**
- [Español](#)

**READINFO****NAME**

ReadInfo -- Return information about the attachments of the message in the active Read window. (V2.0)

**TEMPLATE**

VAR/K,STEM/K

**FUNCTION**

Returns information about the attachments of the message in the active Read window as set by [MAILREAD ?](#).

**INPUTS**

VAR/K - alternative variable to put the results into instead of RESULT  
 STEM/K - base name used for the stems where the results will be stored

**RETURNS**

VAR - info returned by the query  
 <STEM>FILENAME.COUNT - number of parts of the message, excluding the first header block  
 <STEM>FILENAME.NR - filename of the nth part of the message, where nr is a number between 0 and n-1 (0 = first part after the headers, usually the body of the message)  
 <STEM>FILETYPE.NR - content type of the nth part of the message, where nr is a number between 0 and n-1 (0 = first part after the headers, usually the body of the message)  
 <STEM>FILESIZE.NR - size of the nth part of the message, where nr is a number between 0 and n-1 (0 = first part after the headers, usually the body of the message)  
 <STEM>TEMPFILE.NR - temporary file where the nth part of the message is stored, nr being a number between 0 and n-1 (0 = first part after the headers, usually the body of the message)

RC is set to 10 if no Read window was previously specified as "active" with [MAILREAD ?](#).

**NOTES**

No filename is returned for the body of the message.

**EXAMPLE**

/\* Enable result codes \*/

OPTIONS RESULTS

/\* Silently decode the current message \*/

MAILREAD QUIET

/\* Get info about the message, then close the window \*/

READINFO STEM ri.

READCLOSE

/\* Display results \*/

DO i = 0 TO ri.filename.count-1

```
SAY 'Information about part #'i+1
SAY ' File name: 'ri.filename.i
SAY ' File type: 'ri.filetype.i
SAY ' File size: 'ri.filesize.i
SAY ' Stored in: 'ri.tempfile.i
```

END

## BUGS

The command used to blindly act upon the first Read window opened at any given time; this was changed in V2.4 to require the use of [MAILREAD ?](#) to explicitly mark a window as "active".

## SEE ALSO

[MAILREAD ?](#)