

## **Wikiprint Book**

**Title: Documentation/ARexxAPI/READPRINT**

**Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/READPRINT**

**Version: 5**

**Date: 29.01.2015 21:21:52**

## Table of Contents

Languages:	3
READPRINT	3

**Languages:**

- English
- [Español](#)

**READPRINT****NAME**

ReadPrint -- Print a part of the message in the active Read window to the printer. (V2.0)

**TEMPLATE**

PART/N

**FUNCTION**

Sends to the printer a part of the message in the active Read window, as set by [MAILREAD ?](#).

**INPUTS**

PART/N - part of the message to send to the printer, possible values are 1 for the first part of the message (usually the body), 2 or higher for further parts, or no value at all to get a printout of the visible part of the message

**RETURNS**

RC is set to 10 if the specified part does not exist or no Read window was previously specified as "active" with [MAILREAD ?](#).

**NOTES****EXAMPLE**

```
/* Enable result codes */
```

```
OPTIONS RESULTS
```

```
/* Silently decode the current message */
```

```
MAILREAD QUIET
```

```
/* Print the body, then close the message */
```

```
READPRINT 1
```

```
READCLOSE
```

**BUGS**

The command used to blindly act upon the first Read window opened at any given time; this was changed in V2.4 to require the use of [MAILREAD ?](#) to explicitly mark a window as "active".

**SEE ALSO**

[MAILREAD ?](#), [READINFO ?](#)