

## READSAVE

### NAME

ReadSave -- Save a part of the message in the active Read window to a file. (V2.0)

### TEMPLATE

PART/N,FILENAME/K,OVERWRITE/S

### FUNCTION

Saves a part of the message in the active Read window to a file.

### INPUTS

PART/N - part of the message to save, possible values are 1 for the first part of the message (usually the body), 2 or higher for further parts, or no value at all to get a printout of the visible part of the message

FILENAME/K - filename to use

OVERWRITE/S - avoid any security requesters opened due to an already existing file

### RETURNS

RC is set to 10 if the specified part doesn't exist, if the file couldn't be written to or if no Read window was previously specified as "active" with [MAILREAD ?](#).

### NOTES

### EXAMPLE

```
/* Enable result codes */
```

```
OPTIONS RESULTS
```

```
/* Silently decode the current message */
```

```
MAILREAD QUIET
```

```
/* Save the body to a file, then close the message */
```

```
READSAVE 1 FILENAME 'mail:important'
```

```
READCLOSE
```

### BUGS

The command used to blindly act upon the first Read window opened at any given time; this was changed in V2.4 to require the use of [MAILREAD ?](#) to explicitly mark a window as "active".

### SEE ALSO

[MAILREAD ?](#), [READINFO ?](#)