

Wikiprint Book

Title: Documentation/ARexxAPI/READSAVE

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/READSAVE

Version: 5

Date: 28.01.2015 13:11:37

Table of Contents

READSAVE

3

READSAVE

NAME

ReadSave -- Save a part of the message in the active Read window to a file. (V2.0)

TEMPLATE

PART/N,FILENAME/K,OVERWRITE/S

FUNCTION

Saves a part of the message in the active Read window to a file.

INPUTS

PART/N - part of the message to save, possible values are 1 for the first part of the message (usually the body), 2 or higher for further parts, or no value at all to get a printout of the visible part of the message

FILENAME/K - filename to use

OVERWRITE/S - avoid any security requesters opened due to an already existing file

RETURNS

RC is set to 10 if the specified part doesn't exist, if the file couldn't be written to or if no Read window was previously specified as "active" with

[MAILREAD ?](#).

NOTES

EXAMPLE

```
/* Enable result codes */
```

```
OPTIONS RESULTS
```

```
/* Silently decode the current message */
```

```
MAILREAD QUIET
```

```
/* Save the body to a file, then close the message */
```

```
READSAVE 1 FILENAME 'mail:important'
```

```
READCLOSE
```

BUGS

The command used to blindly act upon the first Read window opened at any given time; this was changed in V2.4 to require the use of [MAILREAD ?](#) to explicitly mark a window as "active".

SEE ALSO

[MAILREAD ?](#), [READINFO ?](#)