

Error: Macro TranslatedPages(None) failed

expected string or buffer

ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

49. READCLOSE
50. READINFO
51. READPRINT
52. READSAVE
53. REQUEST
54. REQUESTFILE
55. REQUESTFOLDER
56. REQUESTSTRING
57. RESTART
58. SCREENTOBACK
59. SCREENTOFRONT
60. SETFLAG
61. SETFOLDER
62. SETMAIL
63. SETMAILFILE
64. SHOW
65. USERINFO
66. WRITEATTACH
67. WRITEBCC
68. WRITECC
69. WRITEEDITOR
70. WRITEFROM
71. WRITEIDENTITY
72. WRITELETTER
73. WRITEMAILTO
74. WRITEOPTIONS
75. WRITEQUEUE
76. WRITEREPLYTO
77. WRITESEND
78. WRITESUBJECT
79. WRITETO

REQUEST

NAME

Request -- Open a custom requester. (V1.3.3)

TEMPLATE

VAR/K,STEM/K,BODY/A,GADGETS/A

FUNCTION

Opens a requester containing the supplied body and gadgets, and returns the choice taken by the user.

INPUTS

VAR/K - alternative variable to put the results into instead of RESULT (V2.0)
 STEM/K - base name used for the stem where the result will be stored (V2.0)
 BODY/A - a string containing the body of the requester
 GADGETS/A - a string containing a vertical bar (|) separated list of gadget labels

RETURNS

VAR - info returned by the query
 <STEM>RESULT - number of the selected gadget; may be 0 for the rightmost gadget, 1 for the leftmost gadget, and 2..n for the second, etc. gadget from the left

NOTES

Following the MUI specs, every gadget can have a shortcut by inserting a `_` (underscore) character in front of the character that should be used as shortcut. A default gadget can also be defined with a `*` (asterisk) character in front; the default gadget is activated when pressing the `<Return>` key.

Styles can also be used. See the MUI developer documentation for more info.

Please respect the Amiga User Interface Style Guide when creating requesters. For instance, the rightmost gadget will be triggered by the `<Esc>` key, and should always offer a safe way out.

EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Prepare the text for our requester.
 * Here we have to escape the single '*' (asterisk) via
 * an additional asterisk sign because an asterisk is
 * a reserved character for ARexx itself
 */
body = "Is YAM just great?"
gadgets = "!*_Yeah!|_No way, Outlook rules!|_What is YAM?"

/* Open a custom requester */
REQUEST body gadgets
```

BUGS

SEE ALSO