

## **Wikiprint Book**

**Title: Documentation/ARexxAPI/REQUESTSTRING**

**Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/REQUESTSTRING**

**Version: 5**

**Date: 26.01.2015 11:34:29**

## Table of Contents

Languages:	3
REQUESTSTRING	3

**Languages:**

- **English**
- [Español](#)

**REQUESTSTRING****NAME**

RequestString -- Open a requester asking the user to enter a text string. (V2.0)

**TEMPLATE**

VAR/K,STEM/K,BODY/A,STRING/K,SECRET/S

**FUNCTION**

Opens a requester asking the user to enter a text string.

**INPUTS**

VAR/K - alternative variable to put the results into instead of RESULT

STEM/K - base name used for the stem where the result will be stored

BODY/A - a string containing the body of the requester

STRING/K - optional, text string used by default

SECRET/S - force characters to appear as asterisks (\*)

**RETURNS**

VAR - info returned by the query

<STEM>STRING - text entered in the requester

RC is set to 1 if the user cancels the requester.

**NOTES****EXAMPLE**

```
/* Enable result codes */
```

```
OPTIONS RESULTS
```

```
/* Request the user to type something */
```

```
body = "Please type your name"
```

```
default = "Bill Clinton"
```

```
REQUESTSTRING body STRING default
```

**BUGS****SEE ALSO**