

Wikiprint Book

Title: Documentation/ARexxAPI/SETFOLDER

Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/SETFOLDER

Version: 6

Date: 31.01.2015 14:17:14

Table of Contents

Languages:	3
SETFOLDER	3

Languages:

- **English**
- [Español](#)

SETFOLDER

NAME

SetFolder -- Set the current folder.

TEMPLATE

FOLDER/A

FUNCTION

Makes the named folder the current folder.

INPUTS

FOLDER/A - name, directory or number of the folder to turn into the current folder; folder numbers start counting from 0

RETURNS

RC is set to 10 if the specified folder doesn't exist.

NOTES

In YAM 1.0 - 1.3.2, SETFOLDER could only accept a folder number as argument. This was changed in 1.3.3 to also accept folder names, and again in 2.2 to accept directory names, too. Therefore, to be on the safe side scripts should check the YAM version in use before deciding to use the latter as argument.

Also, bear in mind localization when referring to folders by their name.

EXAMPLE

```
/* Switch to the Outgoing folder */
```

```
SETFOLDER Outgoing
```

```
/* Switch to the first folder in the list */
```

```
SETFOLDER 0
```

BUGS

SEE ALSO

[REQUESTFOLDER ?](#)