

## **Error: Macro TranslatedPages(None) failed**

expected string or buffer

### **ARexx API**

# **WRITEATTACH**

## **NAME**

WriteAttach -- Attach a file to a new message.

## **TEMPLATE**

FILE/A,DESC,ENCMODE,CTYPE

## **FUNCTION**

Attaches a file to a new message.

## **INPUTS**

FILE/A - filename to attach, with path

DESC - optional, string with a description for the file (V1.3)

ENCMODE - optional, encoding type for the file; may be either "uu" or "b64" (V1.3)

CTYPE - optional, content type of the file (V1.3)

## **RETURNS**

RC is set to 10 if no Write window was previously specified as "active" with MAILWRITE ?.

## **NOTES**

By default, binary files are encoded as Base64 (MIME), whereas text files are UUencoded.

The default content type is taken after scanning the built-in list of MIME types and then looking at the MIME types defined in the user configuration. For instance, if the user has defined "application/pgs" as MIME type for files using the ".pgs" extension, all files attached bearing this extension will default to "application/pgs" unless CTYPE overrides this. If no suitable MIME type is found and no content type has been specified, YAM will fallback to "application/octet-stream".

## **EXAMPLE**

```
/* Attach a file */
```

```
MAILWRITE WINDOW 0 /* Set the active Write window */
```

```
WRITEATTACH 'Docs:Mag.pgs' ENCMODE 'b64' CTYPE 'application/pgs'
```

## **BUGS**

No error is returned if the specified file was found but couldn't be opened.

**SEE ALSO**

MAILWRITE ?