

## Error: Macro TranslatedPages(None) failed

expected string or buffer

### ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

49. READCLOSE
50. READINFO
51. READPRINT
52. READSAVE
53. REQUEST
54. REQUESTFILE
55. REQUESTFOLDER
56. REQUESTSTRING
57. RESTART
58. SCREENTOBACK
59. SCREENTOFRONT
60. SETFLAG
61. SETFOLDER
62. SETMAIL
63. SETMAILFILE
64. SHOW
65. USERINFO
66. WRITEATTACH
67. WRITEBCC
68. WRITECC
69. WRITEEDITOR
70. WRITEFROM
71. WRITEIDENTITY
72. WRITELETTER
73. WRITEMAILTO
74. WRITEOPTIONS
75. WRITEQUEUE
76. WRITEREPLYTO
77. WRITESEND
78. WRITESUBJECT
79. WRITETO

## **WRITEATTACH**

### NAME

WriteAttach -- Attach a file to a new message.

### TEMPLATE

FILE/A,DESC,ENCMODE,CTYPE

### FUNCTION

Attaches a file to a new message.

### INPUTS

FILE/A - filename to attach, with path

DESC - optional, string with a description for the file (V1.3)

ENCMODE - optional, encoding type for the file; may be either "uu" or "b64" (V1.3)

CTYPE - optional, content type of the file (V1.3)

### RETURNS

RC is set to 10 if no Write window was previously specified as "active" with MAILWRITE?.

### NOTES

### WRITEATTACH

By default, binary files are encoded as Base64 (MIME), whereas text files are UUencoded.

The default content type is taken after scanning the built-in list of MIME types and then looking at the MIME types defined in the user configuration. For instance, if the user has defined "application/pgs" as MIME type for files using the ".pgs" extension, all files attached bearing this extension will default to "application/pgs" unless CTYPE overrides this. If no suitable MIME type is found and no content type has been specified, YAM will fallback to "application/octet-stream".

#### EXAMPLE

```
/* Set the active Write window */
MAILWRITE WINDOW 0

/* Attach a file */
WRITEATTACH 'Docs:Mag.pgs' ENCMODE 'b64' CTYPE 'application/pgs'
```

#### BUGS

No error is returned if the specified file was found but couldn't be opened.

#### SEE ALSO

MAILWRITE?