Error: Macro TranslatedPages(None) failed

```
expected string or buffer
```

ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

49. READCLOSE
50. READINFO
51. READPRINT
52. READSAVE
53. REQUEST
54. REQUESTFILE
55. REQUESTFOLDER
56. REQUESTSTRING
57. RESTART
58. SCREENTOBACK
59. SCREENTOFRONT
60. SETFLAG
61. SETFOLDER
62. SETMAIL
63. SETMAILFILE
64. SHOW
65. USERINFO
66. WRITEATTACH
67. WRITEBCC
68. WRITECC
69. WRITEEDITOR
70. WRITEFROM
71. WRITEIDENTITY
72. WRITELETTER
73. WRITEMAILTO
74. WRITEOPTIONS
75. WRITEQUEUE
76. WRITEREPLYTO
77. WRITESEND
78. WRITESUBJECT
79. WRITETO

WRITEBCC

NAME

WriteBCC -- Enter one or more names, addresses or aliases into the "Hidden copies to" field of the Write window. (V2.0)

TEMPLATE

ADDRESS/A/M,ADD/S

FUNCTION

Enters one or more names, addresses or aliases into the "Hidden copies to" field of the Write window. YAM will resolve names and aliases looking in the address book.

INPUTS

`ADDRESS/A/M` - list of names/addresses/aliases
`ADD/S` - prevent the new data from replacing the old data already present in the "Hidden copies to" field

RETURNS

`RC` is set to 10 if no Write window was previously specified as "active" with MAILWRITE?.

NOTES

EXAMPLE

```
/* Set the active Write window */
MAILWRITE WINDOW 0

/* Adds some BCC recipients to a message */
'WRITEBCC "George Bush" "j_doe" "carol@example.com" ADD'
```

BUGS

SEE ALSO

MAILWRITE?