

## Error: Macro TranslatedPages(None) failed

expected string or buffer

### ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

- 49. READCLOSE
- 50. READINFO
- 51. READPRINT
- 52. READSAVE
- 53. REQUEST
- 54. REQUESTFILE
- 55. REQUESTFOLDER
- 56. REQUESTSTRING
- 57. RESTART
- 58. SCREENTOBACK
- 59. SCREENTOFRONT
- 60. SETFLAG
- 61. SETFOLDER
- 62. SETMAIL
- 63. SETMAILFILE
- 64. SHOW
- 65. USERINFO
- 66. WRITEATTACH
- 67. WRITEBCC
- 68. WRITECC
- 69. WRITEEDITOR
- 70. WRITEFROM
- 71. WRITEIDENTITY
- 72. WRITELETTER
- 73. WRITEMAILTO
- 74. WRITEOPTIONS
- 75. WRITEQUEUE
- 76. WRITEREPLYTO
- 77. WRITESEND
- 78. WRITESUBJECT
- 79. WRITETO

## WRITEEDITOR

### NAME

WriteEditor -- Pass an ARexx command to the internal editor. (V2.0)

### TEMPLATE

VAR/K,STEM/K,COMMAND/A

### FUNCTION

Passes an ARexx command to the internal editor to act upon the contents of a given Write window.

Quoting the TextEditor.mcc class autdoc, the following commands are currently supported:

```
CLEAR
CUT
COPY
PASTE
ERASE
GOTOLINE      Template: /N/A
GOTOCOLUMN    Template: /N/A
CURSOR        Template: Up/S,Down/S,Left/S,Right/S
LINE          Template: /N/A
COLUMN        Template: /N/A
```

NEXT	Template: Word/S, Sentence/S, Paragraph/S, Page/S
PREVIOUS	Template: Word/S, Sentence/S, Paragraph/S, Page/S
POSITION	Template: SOF/S, EOF/S, SOL/S, EOL/S, SOW/S, EOW/S, SOV/S, EOVS/S
SETBOOKMARK	Template: /N/A
GOTOBOOKMARK	Template: /N/A
TEXT	Template: /F
UNDO	
REDO	
GETLINE	
GETCURSOR	Template: Line/S, Column/S
MARK	Template: On/S, Off/S
DELETE	
BACKSPACE	
KILLLINE	
TOUPPER	
TOLOWER	

Refer to the Amiga User Interface Style Guide for more info about these commands.

Please note that because of the internal use of the ReadArgs() function, the ARexx Host requires to escape certain special characters like a newline (0x0a) or escape character (0x1b) if you want to pass it i.e. with an TEXT command to the texteditor.

This means that you have to use the following escape sequences in your provided strings:

```
*N substitutes to 0x0a
 *E substitutes to 0x1b
 !** substitutes to *
 *" substitutes to "
```

Please have a look at the examples below for a short example on how to use these escape sequences properly.

## INPUTS

VAR/K - alternative variable to put the results into instead of RESULT  
 STEM/K - base name used for the stem where the result will be stored  
 COMMAND/A - the command string to be passed

## RETURNS

VAR - info returned by the query  
 <STEM>RESULT - results of the command, if any

RC is set to 10 if no Write window was previously specified as "active" with MAILWRITE?.

## NOTES

### EXAMPLE

```
/* Enable result codes */
OPTIONS RESULTS

/* Start a new mail */
MAILWRITE STEM st.
win = st.window

/* Edit the Write window */
MAILWRITE WINDOW win
WRITETO 'boss@example.com'
'WRITESUBJECT "I do not think I can go to work today"'

/* Clear the editor */
```

WRITEEDITOR CLEAR

```
/* Write some text into the editor */
```

```
'WRITEEDITOR "TEXT Sorry, but I am sick today!'"
```

```
/* Write some text containing a newline (*N) */
```

```
'WRITEEDITOR "TEXT Hello Joe,*N I would like to meet you."'
```

BUGS

SEE ALSO

MAILWRITE?