

Languages:

- English
- [Español](#)

Table of Contents

Languages:	1
WRITEOPTIONS	2

WRITEOPTIONS

NAME

WriteOptions -- Set the options of a new message. (V2.0)

TEMPLATE

DELETE/S,RECEIPT/S,NOTIF/S,ADDINFO/S,IMPORTANCE/N,SIG/N,SECURITY/N

FUNCTION

Sets the options of a new message.

INPUTS

DELETE/S - discard the message completely after sending

RECEIPT/S - ask for a return receipt

NOTIF/S - enable message tracking (MDN)

ADDINFO/S - add personal information

IMPORTANCE/N - importance of the message, possible values are:

- 0 - high
- 1 - normal (default)
- 2 - low

SIG/N - signature to use, possible values are:

- 0 - no signature
- 1 - default value taken from the Signature configuration
- 2 - alt. signature #1
- 3 - alt. signature #2

SECURITY/N - security to use, possible values are:

- 0 - none
- 1 - PGP signed
- 2 - PGP encrypted
- 3 - PGP signed & encrypted
- 4 - send anonymously
- 5 - default value for this recipient (default)

RETURNS

RC is set to 10 if no Write window was previously specified as "active" with [MAILWRITE](#).

NOTES

Defaults are taken from the program configuration; the default signature may vary depending on whether mailing list support is enabled or not for the current folder. If anonymous send is specified, personal info and signatures are removed automatically.

EXAMPLE

```
/* Set the active Write window */
MAILWRITE WINDOW 0

/* Set a message to be sent anonymously */
WRITEOPTIONS SECURITY 4
```

BUGS

SEE ALSO

[MAILWRITE](#)