

## Error: Macro TranslatedPages(None) failed

expected string or buffer

### ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

49. READCLOSE
50. READINFO
51. READPRINT
52. READSAVE
53. REQUEST
54. REQUESTFILE
55. REQUESTFOLDER
56. REQUESTSTRING
57. RESTART
58. SCREENTOBACK
59. SCREENTOFRONT
60. SETFLAG
61. SETFOLDER
62. SETMAIL
63. SETMAILFILE
64. SHOW
65. USERINFO
66. WRITEATTACH
67. WRITEBCC
68. WRITECC
69. WRITEEDITOR
70. WRITEFROM
71. WRITEIDENTITY
72. WRITELETTER
73. WRITEMAILTO
74. WRITEOPTIONS
75. WRITEQUEUE
76. WRITEREPLYTO
77. WRITESEND
78. WRITESUBJECT
79. WRITETO

## WRITEOPTIONS

### NAME

WriteOptions -- Set the options of a new message. (V2.0)

### TEMPLATE

DELETE/S,RECEIPT/S,NOTIF/S,ADDINFO/S,IMPORTANCE/N,SIG/N,SECURITY/N

### FUNCTION

Sets the options of a new message.

### INPUTS

DELETE/S - discard the message completely after sending

RECEIPT/S - ask for a return receipt

NOTIF/S - enable message tracking (MDN)

ADDINFO/S - add personal information

IMPORTANCE/N - importance of the message, possible values are:

◇ 0 - high

◇ 1 - normal (default)

◇ 2 - low

SIG/N - signature to use, possible values are:

- ◇ 0 - no signature
- ◇ 1 - default value taken from the Signature configuration
- ◇ 2 - alt. signature #1
- ◇ 3 - alt. signature #2

SECURITY/N - security to use, possible values are:

- ◇ 0 - none
- ◇ 1 - PGP signed
- ◇ 2 - PGP encrypted
- ◇ 3 - PGP signed & encrypted
- ◇ 4 - send anonymously
- ◇ 5 - default value for this recipient (default)

## RETURNS

RC is set to 10 if no Write window was previously specified as "active" with MAILWRITE?.

## NOTES

Defaults are taken from the program configuration; the default signature may vary depending on whether mailing list support is enabled or not for the current folder. If anonymous send is specified, personal info and signatures are removed automatically.

## EXAMPLE

```
/* Set the active Write window */
MAILWRITE WINDOW 0

/* Set a message to be sent anonymously */
WRITEOPTIONS SECURITY 4
```

## BUGS

## SEE ALSO

MAILWRITE?