

## **Wikiprint Book**

**Title: Documentation/ARexxAPI/WRITEOPTIONS**

**Subject: YAM - Yet Another Mailer - Documentation/ARexxAPI/WRITEOPTIONS**

**Version: 6**

**Date: 03/03/15 16:11:21**

## Table of Contents

Languages:	3
WRITEOPTIONS	3

**Languages:**

- **English**
- [Español](#)

**WRITEOPTIONS****NAME**

WriteOptions -- Set the options of a new message. (V2.0)

**TEMPLATE**

DELETE/S,RECEIPT/S,NOTIF/S,ADDINFO/S,IMPORTANCE/N,SIG/N,SECURITY/N

**FUNCTION**

Sets the options of a new message.

**INPUTS**

DELETE/S - discard the message completely after sending

RECEIPT/S - ask for a return receipt

NOTIF/S - enable message tracking (MDN)

ADDINFO/S - add personal information

IMPORTANCE/N - importance of the message, possible values are:

- 0 - high
- 1 - normal (default)
- 2 - low

SIG/N - signature to use, possible values are:

- 0 - no signature
- 1 - default value taken from the Signature configuration
- 2 - alt. signature #1
- 3 - alt. signature #2

SECURITY/N - security to use, possible values are:

- 0 - none
- 1 - PGP signed
- 2 - PGP encrypted
- 3 - PGP signed & encrypted
- 4 - send anonymously
- 5 - default value for this recipient (default)

**RETURNS**

RC is set to 10 if no Write window was previously specified as "active" with [MAILWRITE](#).

**NOTES**

Defaults are taken from the program configuration; the default signature may vary depending on whether mailing list support is enabled or not for the current folder. If anonymous send is specified, personal info and signatures are removed automatically.

**EXAMPLE**

```
/* Set the active Write window */
MAILWRITE WINDOW 0

/* Set a message to be sent anonymously */
WRITEOPTIONS SECURITY 4
```

**BUGS****SEE ALSO**

[MAILWRITE](#)