

Error: Macro TranslatedPages(None) failed

expected string or buffer

ARexx Function List

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE
47. NEWMAILFILE
48. QUIT

- 49. READCLOSE
- 50. READINFO
- 51. READPRINT
- 52. READSAVE
- 53. REQUEST
- 54. REQUESTFILE
- 55. REQUESTFOLDER
- 56. REQUESTSTRING
- 57. RESTART
- 58. SCREENTOBACK
- 59. SCREENTOFRONT
- 60. SETFLAG
- 61. SETFOLDER
- 62. SETMAIL
- 63. SETMAILFILE
- 64. SHOW
- 65. USERINFO
- 66. WRITEATTACH
- 67. WRITEBCC
- 68. WRITECC
- 69. WRITEEDITOR
- 70. WRITEFROM
- 71. WRITEIDENTITY
- 72. WRITELETTER
- 73. WRITEMAILTO
- 74. WRITEOPTIONS
- 75. WRITEQUEUE
- 76. WRITEREPLYTO
- 77. WRITESEND
- 78. WRITESUBJECT
- 79. WRITETO

WRITEQUEUE

NAME

WriteQueue -- Put a new message into the Outgoing queue.

TEMPLATE

HOLD/S

FUNCTION

Puts a new, just composed message into the Outgoing queue.

INPUTS

HOLD/S - mark the message as "Hold" to avoid sending it by mistake (V2.0)

RETURNS

RC is set to 10 if no Write window was previously specified as "active" with MAILWRITE?.

NOTES

EXAMPLE

```
/* New mail */
MAILWRITE
```

WRITEQUEUE

```
WRITETO 'boss@example.com'  
'WRITESUBJECT "I do not think I can go to work today"'  
WRITELETTER 'work:excuses.txt'  
WRITEQUEUE
```

BUGS

SEE ALSO

MAILWRITE?, WRITESEND?