

The Trac Configuration File

Error: Macro TracGuideToc(None) failed

```
'NoneType' object has no attribute 'find'
```

Trac configuration is done by editing the `trac.ini` config file, located in `<projectenv>/conf/trac.ini`. Changes to the configuration are usually reflected immediately, though changes to the `[components]` or `[logging]` sections will require restarting the web server. You may also need to restart the web server after creating a global configuration file when none was previously present.

The `trac.ini` configuration file should be writable by the web server, as Trac currently relies on the possibility to trigger a complete environment reload to flush its caches.

Global Configuration

In versions prior to 0.11, the global configuration was by default located in `$prefix/share/trac/conf/trac.ini` or `/etc/trac/trac.ini`, depending on the distribution. If you're upgrading, you may want to specify that file to inherit from. Literally, when you're upgrading to 0.11, you have to add an `[inherit]` section to your project's `trac.ini` file. Additionally, you have to move your customized templates and common images from `$prefix/share/trac/...` to the new location.

Global options will be merged with the environment-specific options, where local options override global options. The options file is specified as follows:

```
[inherit]
file = /path/to/global/trac.ini
```

Multiple files can be specified using a comma-separated list.

Note that you can also specify a global option file when creating a new project, by adding the option `--inherit=/path/to/global/trac.ini` to `trac-admin`'s `initenv` command. If you do not do this but nevertheless intend to use a global option file with your new environment, you will have to go through the newly generated `conf/trac.ini` file and delete the entries that will otherwise override those set in the global file.

There are two more entries in the `[inherit]` section, `templates_dir` for sharing global templates and `plugins_dir`, for sharing plugins. Those entries can themselves be specified in the shared configuration file, and in fact, configuration files can even be chained if you specify another `[inherit]` file there.

Reference for settings

This is a brief reference of available configuration options.

[account-manager]

<code>account_changes_notify_addresses</code>	List of email addresses that get notified of user changes, ie, new user, password change and delete user.	(no default)
<code>allow_delete_account</code>	Allow users to delete their own account.	enabled

auth_init	Launch an initial Trac authentication setup.	enabled
authentication_url	URL of the HTTP authentication service	(no default)
cookie_refresh_pct	Persistent sessions randomly get a new session cookie ID with likelihood in percent per work hour given here (zero equals to never) to decrease vulnerability of long-lasting sessions.	10
db_htdigest_realm	Realm to select relevant htdigest db entries	(no default)
db_ldap_passwd_hash_type	Default hash type of new/updated passwords	crypt
email_regexp	A validation regular expression describing new account emails. Define constraints for a valid email address. A custom pattern can narrow or widen scope i.e. to accept UTF-8 characters.	(?i)^[A-Z0-9._%+-]+@(?:[A-Z0-
environ_auth_overwrite	Whether environment variable REMOTE_USER should get overwritten after processing login form input. Otherwise it will only be set, if unset at the time of authentication.	enabled
force_passwd_change	Force the user to change password when it's reset.	enabled
generated_password_length	Length of the randomly-generated passwords created when resetting the password for an account.	8
hash_method	IPasswordHashMethod used to create new/updated passwords	HtDigestHashMethod
htdigest_file	Path relative to Trac environment or full host machine path to password file	(no default)
htdigest_realm	Realm to select relevant htdigest file entries	(no default)
htpasswd_file	Path relative to Trac environment or full host machine path to password file	(no default)
htpasswd_hash_type	Default hash type of new/updated passwords	crypt
login_opt_list	Set to True, to switch login page style showing alternative actions in a single listing together.	disabled
notify_actions	Comma separated list of actions to notify of. Available actions 'new', 'change', 'delete'.	

password_file	Path to the users file; leave blank to locate the users file by reading svnserve.conf	(no default)
password_store	Ordered list of password stores, queried in turn.	(no default)
persistent_sessions	Allow the user to be remembered across sessions without needing to re-authenticate. This is, user checks a "Remember Me" checkbox and, next time he visits the site, he'll be remembered.	disabled
refresh_passwd	Re-set passwords on successful authentication. This is most useful to move users to a new password store or enforce new store configuration (i.e. changed hash type), but should be disabled/unset otherwise.	disabled
register_basic_question	A question to ask instead of the standard prompt, to which the value of register_basic_token is the answer. Setting to empty string (default value) keeps the standard prompt.	(no default)
register_basic_token	A string required as input to pass verification.	(no default)
register_check	Ordered list of IAccountRegistrationInspector's to use for registration checks.	BasicCheck, EmailCheck, BotT UsernamePermCheck
require_approval	Whether account registration requires administrative approval to enable the account or not.	disabled
reset_password	Set to False, if there is no email system setup.	enabled
username_char_blacklist	Always exclude some special characters from usernames. This is enforced upon new user registration.	: []
username_regexp	A validation regular expression describing new usernames. Define constraints for allowed user names corresponding to local naming policy.	(?i)^[A-Z0-9.\-_{5,}\$
verify_email	Verify the email address of Trac users.	enabled

[attachment]

max_size	Maximum allowed file size (in bytes) for attachments.	262144
max_zip_size	Maximum allowed total size (in bytes) for an attachment list to be downloadable as a .zip. Set this to -1 to disable download as .zip. (since 1.0)	2097152
render_unsafe_content	Whether attachments should be rendered in the browser, or only made downloadable. Pretty much any file may be interpreted as HTML by the browser, which allows a malicious user to attach a file containing cross-site scripting attacks. For public sites where anonymous users can create attachments it is recommended to leave this option disabled (which is the default).	false

[autocomplete]

fields select fields to autocomplete (no default)

[breadcrumbs]

ignore_pattern	Resource names that match this pattern will not be added to the breadcrumbs trail.	(no default)
label	Text label to show before breadcrumb list. If empty, 'Breadcrumbs:' is used as default.	(no default)
max_crumbs	Indicates maximum number of breadcrumbs to store per user.	6
paths	List of URL paths to allow breadcrumb tracking. Globs are supported.	/wiki/, /ticket/, /milestone/

[browser]

color_scale	Enable colorization of the <i>age</i> column. This uses the same color scale as the source code annotation: blue is older, red is newer. (since 0.11)	enabled
downloadable_paths	List of repository paths that can be downloaded. Leave this option empty if you want to disable all downloads, otherwise set it to a comma-separated list of authorized paths (those paths are glob patterns, i.e. "*" can be used as a wild card). In a multi-repository environment, the path must be qualified with the repository name if the path does not point to the default repository (e.g. /reponame/trunk). Note that a simple prefix matching is performed on the paths, so aliases won't get automatically resolved. (since 0.10)	/trunk, /branches/*, /tags/*
hide_properties	Comma-separated list of version control properties to hide from the repository browser. (since 0.9)	svk:merge
intermediate_color	(r,g,b) color triple to use for the color corresponding to the intermediate color, if two linear interpolations are used for the color scale (see <code>intermediate_point</code>). If not set, the intermediate color between <code>oldest_color</code> and <code>newest_color</code> will be used. (since 0.11)	(no default)
intermediate_point	If set to a value between 0 and 1 (exclusive), this will be the point chosen to set the <code>intermediate_color</code>	(no default)

	for interpolating the color value. (<i>since 0.11</i>)	
newest_color	(r,g,b) color triple to use for the color corresponding to the newest color, for the color scale used in <i>blame</i> or the browser <i>age</i> column if <code>color_scale</code> is enabled. (<i>since 0.11</i>)	(255, 136, 136)
oldest_color	(r,g,b) color triple to use for the color corresponding to the oldest color, for the color scale used in <i>blame</i> or the browser <i>age</i> column if <code>color_scale</code> is enabled. (<i>since 0.11</i>)	(136, 136, 255)
oneliner_properties	Comma-separated list of version control properties to render as oneliner wiki content in the repository browser. (<i>since 0.11</i>)	trac:summary
render_unsafe_content	Whether raw files should be rendered in the browser, or only made downloadable. Pretty much any file may be interpreted as HTML by the browser, which allows a malicious user to create a file containing cross-site scripting attacks. For open repositories where anyone can check-in a file, it is recommended to leave this option disabled (which is the default).	false
wiki_properties	Comma-separated list of version control properties to render as wiki content in the repository browser. (<i>since 0.11</i>)	trac:description

[changeset]

max_diff_bytes	Maximum total size in bytes of the modified files (their old size plus their new size) for which the changeset view will attempt to show the diffs inlined (<i>since 0.10</i>).	10000000
max_diff_files	Maximum number of modified files for which the changeset view will attempt to show the diffs inlined (<i>since 0.10</i>).	0
wiki_format_messages	Whether wiki formatting should be applied to changeset messages. If this option is disabled, changeset messages will be rendered as pre-formatted text.	true

[components]

This section is used to enable or disable components provided by plugins, as well as by Trac itself. The component to enable/disable is specified via the name of the option. Whether its enabled is determined by the option value; setting the value to `enabled` or `on` will enable the component, any other value (typically `disabled` or `off`) will disable the component.

The option name is either the fully qualified name of the components or the module/package prefix of the component. The former enables/disables a specific component, while the latter enables/disables any component in the specified package/module.

Consider the following configuration snippet:

```
[components]
trac.ticket.report.ReportModule = disabled
webadmin.* = enabled
```

The first option tells Trac to disable the `report module`. The second option instructs Trac to enable all components in the `webadmin` package. Note that the trailing wildcard is required for module/package matching.

[browser]

To view the list of active components, go to the *Plugins* page on *About Trac* (requires `CONFIG_VIEW` [permissions](#)).

See also: [TracPlugins](#)

[discussion]

<code>default_message_display</code>	Default display mode for topic messages list.	tree
<code>default_topic_display</code>	Default display mode for forum topics list.	classic
<code>forum_sort</code>	Column by which will be sorted forum lists. Possible values are: id, group, name, subject, time, moderators, description, topics, replies, lasttopic, lastreply.	lasttopic
<code>forum_sort_direction</code>	Direction of forum lists sorting. Possible values are: asc, desc.	asc
<code>messages_per_page</code>	Number of messages per page in message list.	50
<code>smtp_always_cc</code>	Always send discussion notifications to the listed e-mail addresses.	
<code>title</code>	Main navigation bar button title.	Discussion
<code>topic_sort</code>	Column by which will be sorted topic lists. Possible values are: id, forum, subject, time, author, body, replies, lastreply.	lastreply
<code>topic_sort_direction</code>	Direction of topic lists sorting. Possible values are: asc, desc.	asc
<code>topics_per_page</code>	Number of topics per page in topic list.	30

[extra-permissions]

This section provides a way to add arbitrary permissions to a Trac environment. This can be useful for adding new permissions to use for workflow actions, for example.

To add new permissions, create a new section `[extra-permissions]` in your `trac.ini`. Every entry in that section defines a meta-permission and a comma-separated list of permissions. For example:

```
[extra-permissions]
EXTRA_ADMIN = EXTRA_VIEW, EXTRA_MODIFY, EXTRA_DELETE
```

This entry will define three new permissions `EXTRA_VIEW`, `EXTRA_MODIFY` and `EXTRA_DELETE`, as well as a meta-permissions `EXTRA_ADMIN` that grants all three permissions.

The permissions are created in upper-case characters regardless of the casing of the definitions in `trac.ini`. For example, the definition `extra_view` would create the permission `EXTRA_VIEW`.

If you don't want a meta-permission, start the meta-name with an underscore (`_`):

```
[extra-permissions]
_perms = EXTRA_VIEW, EXTRA_MODIFY
```

[fullblog]

<code>default_postname</code>	Option for a default naming scheme for new posts. The string can include substitution markers for time (UTC) and user: %Y=year, %m=month, %d=day, %H=hour, %M=minute, %S=second, \$USER. Example template string: %Y/%m/%d/my_topic	(no default)
<code>month_names</code>	Ability to specify a list of month names for display in groupings. If empty it will make a list from default locale setting. Enter list of 12 months like: month_names = January, February, ..., December	(no default)
<code>num_items_front</code>		20

[components]

Option to specify how many recent posts to display on the front page of the Blog (and RSS feeds).

personal_blog When using the Blog as a personal blog (only one author), setting to 'True' will disable the display of 'Browse by author:' in sidebar, and also removes various author links and references. disabled

[googlesitemap]

change_frequency	Change frequency of URLs. Valid values: always, hourly, daily, weekly, monthly, yearly, never. Disabled if empty. (no default)	
compress_sitemap	Send sitemap compressed. Useful for larger sitemaps.	disabled
compression_level	Compression level. Value range: 1 (low) to 9 (high). Default: 6	6
default_priority	Default entry priority.	0.8
ignore_users	Do not list wiki pages from this users (default: "trac")	trac
ignore_wikis	List of wiki pages to not be included in sitemap	(no default)
increased_priority	Increased entry priority.	0.9
list_realms	Which realms should be listed. Supported are "wiki", "ticket", "report", "roadmap", "attachment", "browser", "timeline", "homepage", "contactform" and "fullblog".	wiki, ticket, report, roadmap, attachment,
notify_on	Notify Google about a new sitemap on the listed actions. Valid values are: TICKET_CREATE, TICKET_DELETE, TICKET_MODIFY, WIKI_CREATE, WIKI_DELETE, WIKI_VERSION_DELETE, WIKI_MODIFY, WIKI_RENAME	TICKET_CREATE, TICKET_MODIFY, WIKI_CREATE,
sitemappath	Path of sitemap relative to Trac main URL (default: "sitemap.xml"). If this path ends in .gz the sidemap will automatically be compressed.	sitemap.xml
wiki_auto_priority	Should top hierarchical wiki entries have increased priority automatically?	disabled
wiki_auto_priority_ignore	Which top hierarchical wiki entries should be ignored for	(no default)

- If the targeted Trac is running a version below [?0.10](#) ([?r3526](#) to be precise), then it doesn't know how to dispatch an [InterTrac](#) link, and it's up to the local Trac to prepare the correct link. Not all links will work that way, but the most common do. This is called the compatibility mode, and is `false` by default.
- If you know that the remote Trac knows how to dispatch [InterTrac](#) links, you can explicitly disable this compatibility mode and then *any* [TracLinks](#) can become [InterTrac](#) links.

Example configuration:

```
[intertrac]
# -- Example of setting up an alias:
t = trac

# -- Link to an external Trac:
trac.title = Edgewall's Trac for Trac
trac.url = http://trac.edgewall.org
```

[interwiki]

Every option in the `[interwiki]` section defines one [InterWiki](#) prefix. The option name defines the prefix. The option value defines the URL, optionally followed by a description separated from the URL by whitespace. Parametric URLs are supported as well.

Example:

```
[interwiki]
MeatBall = http://www.usemod.com/cgi-bin/mb.pl?
PEP = http://www.python.org/peps/pep-$1.html Python Enhancement Proposal $1
tsvn = tsvn: Interact with TortoiseSvn
```

[logging]

<code>log_file</code>	If <code>log_type</code> is <code>file</code> , this should be a path to the log-file. Relative paths are resolved relative to the <code>log</code> directory of the environment.	<code>trac.log</code>
<code>log_format</code>	Custom logging format. If nothing is set, the following will be used: <code>Trac[\$(module)s] \$(levelname)s: \$(message)s</code> In addition to regular key names supported by the Python logger library (see ?http://docs.python.org/library/logging.html), one could use: - <code>\$(path)s</code> the path for the current environment - <code>\$(basename)s</code> the last path component of the current environment - <code>\$(project)s</code> the project name Note the usage of <code>\$(...)s</code> instead of <code>%(...)s</code> as the latter form would be interpreted by the <code>ConfigParser</code> itself. Example: <code>\$(thread)d Trac[\$(basename)s:\$(module)s] \$(levelname)s: \$(message)s</code> (<i>since 0.10.5</i>)	(no default)
<code>log_level</code>	Level of verbosity in log. Should be one of (CRITICAL, ERROR, WARN, INFO, DEBUG).	DEBUG
<code>log_type</code>	Logging facility to use. Should be one of (none, file, stderr, syslog, winlog).	none

[mastertickets]

<code>acceptable_formats</code>	The formats that may be chosen; execute <code>dot -T?</code> for a list of options.	<code>png, cmapx</code>
<code>closed_color</code>	Color of closed tickets	<code>green</code>
<code>closed_text</code>	Text for key showing closed tickets	<code>Done</code>
<code>dot_path</code>	Path to the dot executable.	<code>dot</code>
<code>full_graph</code>	Show full dep. graph, not just direct blocking links	<code>disabled</code>
<code>graph_direction</code>	Direction of the dependency graph (TD = Top Down, DT = Down Top, LR = Left Right, RL = Right Left)	<code>TD</code>

[intertrac]

<code>gs_path</code>	Path to the ghostscript executable.	<code>gs</code>
<code>highlight_target</code>	Highlight target tickets in graph	<code>disabled</code>
<code>opened_color</code>	Color of opened tickets	<code>red</code>
<code>opened_text</code>	Text for key showing opened tickets	<code>ToDo</code>
<code>show_key</code>	Show a key for open/closed nodes	<code>disabled</code>
<code>use_gs</code>	If enabled, use ghostscript to produce nicer output.	<code>disabled</code>

[milestone]

<code>stats_provider</code>	Name of the component implementing ITicketGroupStatsProvider, which is used to collect statistics on groups of tickets for display in the milestone views.	<code>DefaultTicketGroupStatsProvider</code>
-----------------------------	--	--

[milestone-groups]

As the workflow for tickets is now configurable, there can be many ticket states, and simply displaying closed tickets vs. all the others is maybe not appropriate in all cases. This section enables one to easily create *groups* of states that will be shown in different colors in the milestone progress bar.

Note that the groups can only be based on the ticket *status*, nothing else. In particular, it's not possible to distinguish between different closed tickets based on the *resolution*.

Example configuration with three groups, *closed*, *new* and *active* (the default only has closed and active):

```
# the 'closed' group correspond to the 'closed' tickets
closed = closed

# .order: sequence number in the progress bar
closed.order = 0

# .query_args: optional parameters for the corresponding
#               query. In this example, the changes from the
#               default are two additional columns ('created' and
#               'modified'), and sorting is done on 'created'.
closed.query_args = group=resolution,order=time,col=id,col=summary,col=owner,col=type,col=priority,col=

# .overall_completion: indicates groups that count for overall
#                       completion percentage
closed.overall_completion = true

new = new
new.order = 1
new.css_class = new
new.label = new

# Note: one catch-all group for other statuses is allowed
active = *
active.order = 2

# .css_class: CSS class for this interval
active.css_class = open

# .label: displayed label for this group
active.label = in progress
```

The definition consists in a comma-separated list of accepted status. Also, '*' means any status and could be used to associate all remaining states to one catch-all group.

[mastertickets]

The CSS class can be one of: new (yellow), open (no color) or closed (green). Other styles can easily be added using custom CSS rule: `table.progress td.<class> { background: <color> }` to a [site/style.css](#) file for example.

(since 0.11)

[mimeviewer]

<code>max_preview_size</code>	Maximum file size for HTML preview. (since 0.9)	262144
<code>mime_map</code>	List of additional MIME types and keyword mappings. Mappings are comma-separated, and for each MIME type, there's a colon (":") separated list of associated keywords or file extensions. (since 0.10)	<code>text/x-dylan:dylan, text/x-idl:ice, text/x-ada:ads:adb</code>
<code>mime_map_patterns</code>	List of additional MIME types associated to filename patterns. Mappings are comma-separated, and each mapping consists of a MIME type and a Python regexp used for matching filenames, separated by a colon (":"). (since 1.0)	<code>text/plain:README INSTALL COPYING.*</code>
<code>pygments_default_style</code>	The default style to use for Pygments syntax highlighting.	<code>trac</code>
<code>pygments_modes</code>	List of additional MIME types known by Pygments. For each, a tuple <code>mimetype:mode:quality</code> has to be specified, where <code>mimetype</code> is the MIME type, <code>mode</code> is the corresponding Pygments mode to be used for the conversion and <code>quality</code> is the quality ratio associated to this conversion. That can also be used to override the default quality ratio used by the Pygments render.	(no default)
<code>tab_width</code>	Displayed tab width in file preview. (since 0.9)	8
<code>treat_as_binary</code>	Comma-separated list of MIME types that should be treated as binary data. (since 0.11.5)	<code>application/octet-stream, application/pdf, application/postscript, application/msword, application/rtf,</code>

[notification]

admit_domains	Comma-separated list of domains that should be considered as valid for email addresses (such as localdomain).	(no default)
always_notify_owner	Always send notifications to the ticket owner (<i>since 0.9</i>).	false
always_notify_reporter	Always send notifications to any address in the <i>reporter</i> field.	false
always_notify_updater	Always send notifications to the person who causes the ticket property change and to any previous updater of that ticket.	true
ambiguous_char_width	Which width of ambiguous characters (e.g. 'single' or 'double') should be used in the table of notification mail. If 'single', the same width as characters in US-ASCII. This is expected by most users. If 'double', twice the width of US-ASCII characters. This is expected by CJK users. (<i>since 0.12.2</i>)	single
batch_subject_template	Like ticket_subject_template but for batch modifications. By default, the template is \$prefix Batch modify: \$tickets_descr. (<i>since 1.0</i>)	\$prefix Batch modify: \$tickets_descr
email_sender	Name of the component implementing IEmailSender. This component is used by the notification system to send emails. Trac currently provides SmtplibEmailSender for connecting to an SMTP server, and SendmailEmailSender for running a sendmail-compatible executable. (<i>since 0.12</i>)	SmtplibEmailSender
ignore_domains	Comma-separated list of domains that should not be considered part of email addresses (for usernames with Kerberos domains).	(no default)
mime_encoding	Specifies the MIME encoding scheme for emails. Valid options are 'base64' for Base64 encoding, 'qp' for Quoted-Printable, and 'none' for no encoding, in which case mails will be sent as 7bit if the content is all ASCII, or 8bit otherwise. (<i>since 0.10</i>)	none
sendmail_path	Path to the sendmail executable. The sendmail program must accept the <i>-i</i> and <i>-f</i> options. (<i>since 0.12</i>)	sendmail
smtp_always_bcc	Email address(es) to always send notifications to, addresses do not appear publicly (Bcc 😊). (<i>since 0.10</i>)	(no default)
smtp_always_cc	Email address(es) to always send notifications to, addresses can be seen by all recipients (Cc 😊).	(no default)
smtp_default_domain	Default host/domain to append to address that do not specify one.	(no default)
smtp_enabled	Enable email notification.	false
smtp_from	Sender address to use in notification emails.	trac@localhost
smtp_from_author		false

[notification]

	Use the action author as the sender of notification emails. (<i>since 1.0</i>)	
smtp_from_name	Sender name to use in notification emails.	(no default)
smtp_password	Password for SMTP server. (<i>since 0.9</i>)	(no default)
smtp_port	SMTP server port to use for email notification.	25
smtp_replyto	Reply-To address to use in notification emails.	trac@localhost
smtp_server	SMTP server hostname to use for email notifications.	localhost
smtp_subject_prefix	Text to prepend to subject line of notification emails. If the setting is not defined, then the [\$project_name] prefix. If no prefix is desired, then specifying an empty option will disable it. (<i>since 0.10.1</i>)	__default__
smtp_user	Username for SMTP server. (<i>since 0.9</i>)	(no default)
ticket_subject_template	A Genshi text template snippet used to get the notification subject. By default, the subject template is \$prefix #ticket.id: \$summary. \$prefix being the value of the smtp_subject_prefix option. (<i>since 0.11</i>)	\$prefix #ticket.id: \$summary
use_public_cc	Recipients can see email addresses of other CC'ed recipients. If this option is disabled (the default), recipients are put on BCC. (<i>since 0.10</i>)	false
use_short_addr	Permit email address without a host/domain (i.e. username only). The SMTP server should accept those addresses, and either append a FQDN or use local delivery. (<i>since 0.10</i>)	false
use_tls	Use SSL/TLS to send notifications over SMTP. (<i>since 0.10</i>)	false

[piwik]

piwik_admin_logging	Disabling this option will prevent all logged in admins from showing up on your Google Analytics reports.	disabled
piwik_authenticated_logging	Disabling this option will prevent all authenticated users from showing up on your Google Analytics reports.	enabled
piwik_baseurl	The base url of your Piwik installation. You can find it in the pkBaseURL variable in the Javascript snippet from Piwik.	(no default)
piwik_extensions	Enter any extensions of files you would like to be tracked as a download. For example to track all MP3s and PDFs enter: mp3 pdf	7z aac arc arj asf asx avi bin csv doc

piwik_siteid Piwik's Site ID. (no default)
[project]

admin E-Mail address of the project's administrator. (no default)

admin_trac_url Base URL of a Trac instance where errors in this Trac should be reported. This can be an absolute or relative URL, or '.' to reference this Trac instance. An empty value will disable the reporting buttons. (*since 0.11.3*)

descr Short description of the project. My example project

footer Page footer text (right-aligned). Visit the Trac open source project at <http://trac.edgewall.org/>

icon URL of the icon of the project. common/trac.ico

name Name of the project. My Project

url URL of the main project web site, usually the website in which the base_url resides. This is used in notification e-mails. (no default)

[query]

default_anonymous_query The default query for anonymous users. The query is either in query language syntax, or a URL query string starting with ? as used in query: Trac links. (*since 0.11.2*) status!=closed&cc~=\$USER

default_query	The default query for authenticated users. The query is either in <u>query language</u> syntax, or a URL query string starting with ? as used in query: <u>Trac links</u> . (since 0.11.2)	status!=closed&owner=\$USER
items_per_page	Number of tickets displayed per page in ticket queries, by default (since 0.11)	100
ticketlink_query	The base query to be used when linkifying values of ticket fields. The query is a URL query string starting with ? as used in query: <u>Trac links</u> . (since 0.12)	?status!=closed

[quiet]

enter_label Enter Quiet Mode
 leave_label Leave Quiet Mode

[report]

items_per_page	Number of tickets displayed per page in ticket reports, by default (since 0.11)	100
items_per_page_rss	Number of tickets displayed in the rss feeds for reports (since 0.11)	0

[repositories]

One of the alternatives for registering new repositories is to populate the [repositories] section of the trac.ini.

This is especially suited for setting up convenience aliases, short-lived repositories, or during the initial phases of an installation.

See TracRepositoryAdmin for details about the format adopted for this section and the rest of that page for the other alternatives.

(since 0.12)

[revisionlog]

default_log_limit	Default value for the limit argument in the <u>TracRevisionLog</u> . (since 0.11)	100
graph_colors	Comma-separated list of colors to use for the <u>TracRevisionLog</u> graph display. (since 1.0)	#cc0, #0c0, #0cc, #00c, #c0c, #c00

[roadmap]

stats_provider	Name of the component implementing ITicketGroupStatsProvider, which is used to collect statistics on groups of tickets for display in the roadmap views.	DefaultTicketGroupStatsProvider
----------------	--	---------------------------------

[screenshots]

additional_tags	Additional tags that will be created for submitted	author, components, versions, name
-----------------	--	------------------------------------

	screenshots. Possible values are: author, components, versions, name, description.	
default_components	List of components enabled by default.	all
default_description	Template for embended image description.	\$description
default_filter_relation	Logical relation between component and version part of screenshots filter.	or
default_format	Default format for screenshot download links.	html
default_list_item	Default format of list item description of [[ScreenshotsList()]] macro.	\$id - \$name - \$description
default_order_directions	List of ordering directions for fields specified in default_orders configuration option.	asc
default_orders	List of names of database fields that are used to sort screenshots.	id
default_versions	List of versions enabled by default.	all
ext	List of screenshot file extensions that can be uploaded. Must be supported by PIL.	jpg, png
formats	List of allowed formats for screenshot download.	raw, html, jpg, png
mainnav_title	Main navigation bar button title.	Screenshots
metanav_title	Meta navigation bar link title.	(no default)
path	Path where to store uploaded screenshots.	../screenshots

[screenshots-matrix]

columns	Number of screenshot columns.	3
height	Height of screenshot preview.	120
rows	Number of screenshot preview rows.	3
width	Width of screenshot preview.	160

[search]

default_disabled_filters	Specifies which search filters should be disabled by default on the search page. This will also restrict the filters for the quick search function. The filter names defined by default components are: wiki, ticket, milestone and changeset. For plugins, look for their implementation of the ISearchSource interface, in the get_search_filters() method, the first member of returned	(no default)
--------------------------	--	--------------

tuple. Once disabled, search filters can still be manually enabled by the user on the search page. (since 0.12)

`min_query_length` Minimum length of query string allowed when performing a search. 3

[simpleticket]

`fields` Fields to hide for the simple ticket entry form. (no default)

`show_only` If True, show only the specified fields rather than hiding the specified fields disabled

[spam-filter]

This section is used to handle all configurations used by spam filter plugin.

<code>akismet_api_key</code>	Wordpress key required to use the Akismet API.	(no default)
<code>akismet_api_url</code>	URL of the Akismet service.	<code>rest.akismet.com/1.1/</code>
<code>akismet_karma</code>	By how many points an Akismet reject impacts the overall karma of a submission.	10
<code>attachment_karma</code>	The karma given to attachments.	0
<code>attachment_sample_size</code>	The maximum number of bytes from an attachment to pass through the spam filters.	16384
<code>authenticated_karma</code>	The karma given to authenticated users, in case <code>trust_authenticated</code> is false.	20
<code>badcontent_file</code>	Local file to be loaded to get BadContent. Can be used in addition to BadContent wiki page.	(no default)
<code>bayes_karma</code>	By what factor Bayesian spam probability score affects the overall karma of a submission.	15
<code>bayes_min_training</code>	The minimum number of submissions in the training database required for the filter to start impacting the karma of submissions.	25
<code>blogspam_api_url</code>	URL of the BlogSpam service.	<code>test.blogspam.net:8888</code>
<code>blogspam_karma</code>	By how many points an BlogSpam reject impacts the overall karma of a submission.	5
<code>blogspam_skip_tests</code>	Comma separated list of	<code>bayesian, linksleeve, sfs</code>

	tests to skip.	
botscout_api_key	API key required to use BotScout.	(no default)
botscout_karma	By how many points a BotScout reject impacts the overall karma of a submission.	3
captcha	CAPTCHA method to use for verifying humans.	ExpressionCaptcha
captcha_areyouahuman_host	Host name for AreYouAHuman usage.	ws.areyouahuman.com
captcha_areyouahuman_publisher_key	Publisher key for AreYouAHuman usage.	(no default)
captcha_areyouahuman_scoring_key	Scoring key for AreYouAHuman usage.	(no default)
captcha_expression_ceiling	Maximum value of individual terms in numeric CAPTCHA expression.	10
captcha_expression_terms	Number of terms in numeric CAPTCHA expression.	3
captcha_failed_karma	By how many points a failed CAPTCHA impacts the overall score.	1
captcha_image_alphabet	Alphabet to choose image CAPTCHA challenge from.	abcdefghijklmnopqrstuvwxyz
captcha_image_font_size	Font size to use in image CAPTCHA.	25
captcha_image_fonts	Set of fonts to choose from when generating image CAPTCHA.	vera.ttf
captcha_image_letters	Number of letters to use in image CAPTCHA challenge.	6
captcha_karma	By how many points a successful CAPTCHA response increases the overall score.	20
captcha_karma_lifetime	Time in seconds that a successful CAPTCHA response increases karma.	86400
captcha_keycaptcha_private_key	Private key for KeyCaptcha usage.	(no default)
captcha_keycaptcha_user_id	User id for KeyCaptcha usage.	(no default)
captcha_lifetime	Time in seconds before database cleanup is called.	3600
captcha_recaptcha_private_key	Private key for reCaptcha usage.	(no default)
captcha_recaptcha_public_key		(no default)

	Public key for reCaptcha usage.	
defensio_api_key	Defensio key required to use the API.	(no default)
defensio_api_url	URL of the Defensio service.	api.defensio.com/2.0/users/
defensio_karma	By how many points a Defensio reject impacts the overall karma of a submission.	2
extlinks_allowed_domains	List of domains that should be allowed in external links	example.com, example.org
extlinks_karma	By how many points too many external links in a submission impact the overall score.	2
fspamlist_api_key	API key required to use FSpamList.	(no default)
fspamlist_karma	By how many points a FSpamList reject impacts the overall karma of a submission.	3
httpbl_api_key	Http:BL API key required for use.	(no default)
httpbl_spammer_karma	By how many points listing as "comment spammer" impacts the overall karma of a submission.	6
ip_blacklist_karma	By how many points blacklisting by a single server impacts the overall karma of a submission.	5
ip_blacklist_servers	Servers used for IP blacklisting.	list.blogspambl.com, all.s5h.net, dnsbl.tornevall.org
ip_throttle_karma	By how many points exceeding the configured maximum number of posts per hour impacts the overall score.	3
ipbadcontent_file	Local file to be loaded to get BadIP. Can be used in addition to BadIP wiki page.	(no default)
ipregex_karma	By how many points a match with a pattern on the BadIP page impacts the overall karma of a submission.	20
is_forwarded		false

	Interpret X-Forwarded-For header for IP checks.	
linksleeve_karma	By how many points a LinkSleeve reject impacts the overall karma of a submission.	3
logging_enabled	Whether all content submissions and spam filtering activity should be logged to the database.	true
max_external_links	The maximum number of external links allowed in a submission until that submission gets negative karma.	4
max_posts_by_ip	The maximum allowed number of submissions per hour from a single IP address. If this limit is exceeded, subsequent submissions get negative karma.	10
min_karma	The minimum score required for a submission to be allowed.	0
purge_age	The number of days after which log entries should be purged.	7
regex_karma	By how many points a match with a pattern on the BadContent page impacts the overall karma of a submission.	5
reject_handler	The handler used to reject content.	FilterSystem
report_pages	List of page types to add spam report link	wiki, attachment, ticket
session_karma	By how many points an existing and configured session improves the overall karma of the submission. A third of the points is granted for having an existing session at all, the other two thirds are granted when the user has his name and/or email address set in the session, respectively.	9
show_blacklisted	Show the matched bad content patterns in rejection message.	true

show_blacklisted_ip	Show the matched bad IP patterns in rejection message.	true
show_train_only	Show the buttons for training without deleting entry.	disabled
skip_external	Skip external calls when this negative karma is already reached by internal tests.	20
skip_externalham	Skip external calls when this positive karma is already reached by internal tests.	30
spam_monitor_entries	How many monitor entries are displayed by default (between 5 and 10000).	100
spam_report_entries	How many report entries are displayed by default (between 5 and 10000).	100
spam_user_defaultmode	Default mode for spam user admin panel.	overview
spam_user_maxage	How many days no login are considered for dead accounts.	200
spam_user_minwiki	How many wiki edits are still an unused account.	0
stop_external	Stop external calls when this negative karma is reached.	50
stop_externalham	Stop external calls when this positive karma is reached.	50
stopforumspam_api_key	API key used to report SPAM.	(no default)
stopforumspam_karma	By how many points a StopForumSpam reject impacts the overall karma of a submission.	4
train_external	Allow training of external services.	true
trap_karma	By how many points a trap reject impacts the overall karma of a submission.	10
trap_name	Name of the invisible trap field, should contain some reference to e-mail for better results.	sfp_email
trap_name_hidden	Name of the hidden trap field, should contain some	sfph_mail

	reference to e-mail for better results.	
	Whether content submissions by authenticated users should be trusted without checking for potential spam or other abuse.	false
trust_authenticated		
	Allow usage of external services.	true
use_external		

[sqlite]

extensions Paths to sqlite extensions, relative to Trac environment's directory or absolute. (*since 0.12*) (no default)

[svn]

branches	Comma separated list of paths categorized as branches. If a path ends with '*', then all the directory entries found below that path will be included. Example: /trunk, /branches/*, /projectAlpha/trunk, /sandbox/*	trunk, branches/*
eol_style	End-of-Line character sequences when svn:eol-style property is native. If native (the default), substitute with the native EOL marker on the server. Otherwise, if LF, CRLF or CR, substitute with the specified EOL marker. (<i>since 1.0.2</i>)	native
repository_url	base URL of svn repository	(no default)
tags	Comma separated list of paths categorized as tags. If a path ends with '*', then all the directory entries found below that path will be included. Example: /tags/*, /projectAlpha/tags/A-1.0, /projectAlpha/tags/A-v1.1	tags/*

[svn:externals]

The [TracBrowser](#) for Subversion can interpret the `svn:externals` property of folders. By default, it only turns the URLs into links as Trac can't browse remote repositories.

However, if you have another Trac instance (or an other repository browser like [?ViewVC](#)) configured to browse the target repository, then you can instruct Trac which other repository browser to use for which external URL. This mapping is done in the `[svn:externals]` section of the [TracIni](#).

Example:

```
[svn:externals]
1 = svn://server/repos1 http://trac/proj1/browser/$path?rev=$rev
2 = svn://server/repos2 http://trac/proj2/browser/$path?rev=$rev
3 = http://theirserver.org/svn/eng-soft http://ourserver/viewvc/svn/$path/?pathrev=25914
4 = svn://anotherserver.com/tools_repository http://ourserver/tracs/tools/browser/$path?rev=$rev
```

With the above, the `svn://anotherserver.com/tools_repository/tags/1.1/tools` external will be mapped to `http://ourserver/tracs/tools/browser/tags/1.1/tools?rev=` (and `rev` will be set to the appropriate revision number if the external additionally specifies a revision, see the [?SVN Book on externals](#) for more details).

Note that the number used as a key in the above section is purely used as a place holder, as the URLs themselves can't be used as a key due to various limitations in the configuration file parser.

Finally, the relative URLs introduced in [?Subversion 1.5](#) are not yet supported.

(since 0.11)

[tags]

<code>cloud_caseless_sort</code>	Whether the tag cloud should be sorted case-sensitive.	disabled
<code>cloud_mincount</code>	Integer threshold to hide tags with smaller count.	1
<code>complete_field</code>	Ticket field to which a drop-down tag list should be attached.	keywords
<code>complete_matchcontains</code>	Include partial matches in suggestion list. Default is true.	enabled
<code>complete_sticky_tags</code>	A list of comma separated values available for input.	(no default)
<code>default_format</code>	Set the default format for the handler of the <code>/tags</code> domain. <code> oldlist</code> (default value) <code> The original format with a bulleted-list of "linked-id description (tags)"</code> <code> compact</code> <code> bulleted-list of "linked-description" table</code> <code> table...</code> (see corresponding column option) <code> </code>	oldlist
<code>default_table_cols</code>	Select columns and order for table format using a " "-separated list of column names. Supported columns: realm, id, description, tags	id description tags
<code>exclude_realms</code>	Comma-separated list of realms to exclude from tags queries by default, unless specifically included using "realm:realm-name" in a query.	
<code>ignore_closed_tickets</code>	Do not collect tags from closed tickets.	enabled
<code>listtagged_default_format</code>	Set default format for the handler of the <code>/tags</code> domain. See <code>ListTagged</code> description (WikiMacros) for supported values.	oldlist
<code>listtagged_default_table_cols</code>	Select columns and column order for table format. See <code>ListTagged</code> description (WikiMacros) for supported values.	id description tags
<code>listtagged_exclude_realms</code>	Comma-separated list of realms to exclude from tags queries by default, unless specifically included using 'realm:<realm>' in a query.	
<code>listtagged_items_per_page</code>	Number of tagged resources displayed per page of tag query results requested by <code>ListTagged</code> macros and from <code>/tags</code> .	100

query_exclude_wiki_templates	Whether tagged wiki page templates should be queried.	enabled
revisable_realms	Comma-separated list of realms requiring tag change history.	wiki
separator	Character(s) to use as separators between tags. Default is a single whitespace.	
ticket_fields	List of ticket fields to expose as tags.	keywords
ticket_help	If specified, 'keywords' label on ticket view will be turned into a link to this URL.	(no default)
ticket_help_newwindow	If true and keywords_help specified, wiki page will open in a new window. Default is false.	disabled
wiki_page_link	Link a tag to the wiki page with same name, if it exists.	enabled
wiki_page_prefix	Prefix for tag wiki page names.	(no default)

[ticket]

commit_ticket_update_check_perms	Check that the committer has permission to perform the requested operations on the referenced tickets. This requires that the user names be the same for Trac and repository operations.	true
commit_ticket_update_commands.close	Commands that close tickets, as a space-separated list.	close closed closes fix fixed fixes
commit_ticket_update_commands.refs	Commands that add a reference, as a space-separated list. If set to the special value <ALL>, all tickets referenced by the message will get a reference to the changeset.	addresses re references refs see
commit_ticket_update_envelope	Require commands to be enclosed in an envelope. Must be empty or contain two characters. For example, if set to "[]", then commands must be in the form of [closes #4].	(no default)

commit_ticket_update_notify	Send ticket change notification when updating a ticket.	true
default_cc	Default cc: list for newly created tickets.	(no default)
default_component	Default component for newly created tickets.	(no default)
default_description	Default description for newly created tickets.	(no default)
default_keywords	Default keywords for newly created tickets.	(no default)
default_milestone	Default milestone for newly created tickets.	(no default)
default_owner	Default owner for newly created tickets.	< default >
default_priority	Default priority for newly created tickets.	major
default_resolution	Default resolution for resolving (closing) tickets (<i>since 0.11</i>).	fixed
default_severity	Default severity for newly created tickets.	(no default)
default_summary	Default summary (title) for newly created tickets.	(no default)
default_type	Default type for newly created tickets (<i>since 0.9</i>).	defect
default_version	Default version for newly created tickets.	(no default)
max_comment_size	Maximum allowed comment size in characters. (<i>since 0.11.2</i>).	262144
max_description_size	Maximum allowed description size in characters. (<i>since 0.11</i>).	262144
max_summary_size	Maximum allowed summary size in characters. (<i>since 1.0.2</i>).	262144
pending_removal_status	Status to apply when removing 'Pending' status automatically.	new
preserve_newlines	Whether Wiki formatter should	default

restrict_owner	<p>respect the new lines present in the Wiki text. If set to 'default', this is equivalent to 'yes' for new environments but keeps the old behavior for upgraded environments (i.e. 'no'). (<i>since 0.11</i>).</p> <p>Make the owner field of tickets use a drop-down menu. Be sure to understand the performance implications before activating this option. See Assign-to as Drop-Down List. Please note that e-mail addresses are not obfuscated in the resulting drop-down menu, so this option should not be used if e-mail addresses must remain protected. (<i>since 0.9</i>)</p>	false
workflow	<p>Ordered list of workflow controllers to use for ticket actions (<i>since 0.11</i>).</p>	ConfigurableTicketWorkflow

[ticket-custom]

In this section, you can define additional fields for tickets. See [TracTicketsCustomFields](#) for more details.

[ticket-workflow]

The workflow for tickets is controlled by plugins. By default, there's only a `ConfigurableTicketWorkflow` component in charge. That component allows the workflow to be configured via this section in the `trac.ini` file. See [TracWorkflow](#) for more details.

(*since 0.11*)

[ticketmoderator]

default_moderator	<p>The default moderator for ticket modifications that require moderation, used if the ticket owner and default component owner are not Moderators (<i>since 0.2</i>).</p>	(no default)
ignore_smtp_always	<p>If true (default) email sent to the ticket moderator will not be sent to</p>	enabled

	the <code>smtp_always_cc</code> or <code>smtp_always_bcc</code> addresses (<i>since 0.5</i>).	
<code>moderation_notice</code>	Notice displayed to users who will be subject to moderation when creating or editing tickets (<i>since 0.6.4</i>).	<code>\$submission_type</code> you submit will be routed for moderation. <code>\$login_request</code>
<code>review_promise</code>	Text displayed as part of the default confirmation indicating the moderators expected response time (<i>since 0.6</i>).	We make every effort to review submissions within one working day.
<code>show_moderator_email</code>	Publish the assigned Moderator's e-mail address as part of the response to the submitter (<i>since 0.2</i>).	disabled
<code>subject_template</code>	A Genshi text template snippet used to get the notification subject (<i>since 0.2</i>).	<code>\$prefix [Moderate] \${new and 'New Ticket' or 'Comment'}: \$summary</code>
<code>unmoderated_attachments</code>	Allow users requiring moderation to submit ticket attachments without moderation (<i>since 0.3</i> ; deprecated in 0.4, use <code>MODERATOR_PASS_ATTACH</code> permission).	disabled

[**timeline**]

<code>abbreviated_messages</code>	Whether wiki-formatted event messages should be truncated or not. This only affects the default rendering, and can be overridden by specific event providers, see their own documentation. (<i>Since 0.11</i>)	enabled
<code>changeset_collapse_events</code>	Whether consecutive changesets from the same author having exactly the same message should be presented as one event. That event will link to the range of changesets in the log view. (<i>since 0.11</i>)	false
<code>changeset_long_messages</code>	Whether wiki-formatted changeset messages should be multiline or not. If this option is not specified or is false and <code>wiki_format_messages</code> is set to true, changeset messages will be single line only, losing some formatting (bullet points, etc).	false
<code>changeset_show_files</code>	Number of files to show (-1 for unlimited, 0 to disable). This can also be <code>location</code> , for showing the common prefix for the changed files. (<i>since 0.11</i>).	0
<code>default_daysback</code>	Default number of days displayed in the Timeline, in days. (<i>since 0.9</i> .)	30
<code>max_daysback</code>	Maximum number of days (-1 for unlimited) displayable in the Timeline. (<i>since 0.11</i>)	90
<code>newticket_formatter</code>	Which formatter flavor (e.g. 'html' or 'oneliner') should be used when presenting the description for new tickets. If 'oneliner', the [<code>timeline</code>] <code>abbreviated_messages</code> option applies. (<i>since 0.11</i>).	oneliner
<code>ticket_show_details</code>	Enable the display of all ticket changes in the timeline, not only open / close operations (<i>since 0.9</i>).	false

[trac]

auth_cookie_lifetime	Lifetime of the authentication cookie, in seconds. This value determines how long the browser will cache authentication information, and therefore, after how much inactivity a user will have to log in again. The default value of 0 makes the cookie expire at the end of the browsing session. (<i>since 0.12</i>)	0
auth_cookie_path	Path for the authentication cookie. Set this to the common base path of several Trac instances if you want them to share the cookie. (<i>since 0.12</i>)	(no d
authz_file	The path to the Subversion ?authorization (authz) file . To enable authz permission checking, the AuthzSourcePolicy permission policy must be added to [trac] permission_policies.	(no c
authz_module_name	The module prefix used in the authz_file for the default repository. If left empty, the global section is used.	(no c
auto_preview_timeout	Inactivity timeout in seconds after which the automatic wiki preview triggers an update. This option can contain floating-point values. The lower the setting, the more requests will be made to the server. Set this to 0 to disable automatic preview. The default is 2.0 seconds. (<i>since 0.12</i>)	2.0
auto_reload	Automatically reload template files after modification.	dis
backup_dir	Database backup location	db
base_url	Reference URL for the Trac deployment. This is the base URL that will be used when producing documents that will be used outside of the web browsing context, like for example when inserting URLs pointing to Trac resources in notification e-mails.	(no c
check_auth_ip	Whether the IP address of the user should be checked for authentication (<i>since 0.9</i>).	fal
database	Database connection <u>string</u> for this project	sql
debug_sql	Show the SQL queries in the Trac log, at DEBUG level. (<i>Since 0.11.5</i>)	dis
default_charset		utf
default_date_format	The date format. Valid options are 'iso8601' for selecting ISO 8601 format, or leave it empty which means the default date format will be inferred from the browser's default language. (<i>since 1.0</i>)	(no c
default_dateinfo_format	The date information format. Valid options are 'relative' for displaying relative format and 'absolute' for displaying absolute format. (<i>since 1.0</i>)	rel
default_handler	Name of the component that handles requests to the base URL. Options include TimelineModule, RoadmapModule, BrowserModule, QueryModule, ReportModule, TicketModule and WikiModule. The default is WikiModule. (<i>since 0.9</i>)	Wik
default_language	The preferred language to use if no user preference has been set. (<i>since 0.12.1</i>)	(no c
default_timezone	The default timezone to use	(no c
genshi_cache_size	The maximum number of templates that the template loader will cache in memory. The default value is 128. You may want to choose a higher value if your site uses a larger number of templates, and you have enough memory to spare, or you can reduce it if you are short on memory.	128
htdocs_location	Base URL for serving the core static resources below /chrome/common/. It can be left empty, and Trac will simply serve those resources itself. Advanced users can use this together with trac-admin ... deploy <deploydir> to allow serving the static resources for Trac directly from the web server. Note however that this only applies to the <deploydir>/htdocs/common directory, the other deployed resources	(no c

	(i.e. those from plugins) will not be made available this way and additional rewrite rules will be needed in the web server.	
ignore_auth_case	Whether login names should be converted to lower case (<i>since 0.9</i>).	fal
jquery_location	Location of the jQuery JavaScript library (version 1.7.2). An empty value loads jQuery from the copy bundled with Trac. Alternatively, jQuery could be loaded from a CDN, for example: ?http://code.jquery.com/jquery-1.7.2.min.js , ?http://ajax.aspnetcdn.com/ajax/jquery/jquery-1.7.2.min.js or ?https://ajax.googleapis.com/ajax/libs/jquery/1.7.2/jquery.min.js . (<i>since 1.0</i>)	(no
jquery_ui_location	Location of the jQuery UI JavaScript library (version 1.8.21). An empty value loads jQuery UI from the copy bundled with Trac. Alternatively, jQuery UI could be loaded from a CDN, for example: ?https://ajax.googleapis.com/ajax/libs/jqueryui/1.8.21/jquery-ui.min.js or ?http://ajax.aspnetcdn.com/ajax/jquery.ui/1.8.21/jquery-ui.min.js . (<i>since 1.0</i>)	(no
jquery_ui_theme_location	Location of the theme to be used with the jQuery UI JavaScript library (version 1.8.21). An empty value loads the custom Trac jQuery UI theme from the copy bundled with Trac. Alternatively, a jQuery UI theme could be loaded from a CDN, for example: ?https://ajax.googleapis.com/ajax/libs/jqueryui/1.8.21/themes/start/jquery-ui.css or ?http://ajax.aspnetcdn.com/ajax/jquery.ui/1.8.21/themes/start/jquery-ui.css . (<i>since 1.0</i>)	(no
mainnav	Order of the items to display in the mainnav navigation bar, listed by IDs. See also TracNavigation .	wik bro new
metanav	Order of the items to display in the metanav navigation bar, listed by IDs. See also TracNavigation .	log hel
mysqldump_path	Location of mysqldump for MySQL database backups	mys
never_obfuscate_mailto	Never obfuscate mailto: links explicitly written in the wiki, even if show_email_addresses is false or the user has not the EMAIL_VIEW permission (<i>since 0.11.6</i>).	fal
permission_policies	List of components implementing IPermissionPolicy, in the order in which they will be applied. These components manage fine-grained access control to Trac resources. Defaults to the DefaultPermissionPolicy (pre-0.11 behavior) and LegacyAttachmentPolicy (map ATTACHMENT_* permissions to realm specific ones)	Def Leg
permission_store	Name of the component implementing IPermissionStore, which is used for managing user and group permissions.	Def
pg_dump_path	Location of pg_dump for Postgres database backups	pg
repository_dir	Path to the default repository. This can also be a relative path (<i>since 0.11</i>). This option is deprecated, and repositories should be defined in the repositories section, or using the "Repositories" admin panel. (<i>since 0.12</i>)	(no
repository_sync_per_request	List of repositories that should be synchronized on every page request. Leave this option empty if you have set up post-commit hooks calling trac-admin \$ENV changeset added on all your repositories (recommended). Otherwise, set it to a comma-separated list of repository names. Note that this will negatively affect performance, and will prevent changeset listeners from receiving events from the repositories specified here. The default is to synchronize the default repository, for backward compatibility. (<i>since 0.12</i>)	(de
repository_type	Default repository connector type. (<i>since 0.10</i>) This is also used as the default repository type for repositories defined in TracIni#repositories-section repositories or using the "Repositories" admin panel. (<i>since 0.12</i>)	svn

request_filters	Ordered list of filters to apply to all requests (<i>since 0.10</i>).	(no default)
resizable_textareas	Make <textarea> fields resizable. Requires JavaScript. (<i>since 0.12</i>)	true
secure_cookies	Restrict cookies to HTTPS connections. When true, set the <code>secure</code> flag on all cookies so that they are only sent to the server on HTTPS connections. Use this if your Trac instance is only accessible through HTTPS. (<i>since 0.11.2</i>)	disabled
show_email_addresses	Show email addresses instead of usernames. If false, we obfuscate email addresses. (<i>since 0.11</i>)	false
show_ip_addresses	Show IP addresses for resource edits (e.g. wiki). (<i>since 0.11.3</i>)	false
timeout	Timeout value for database connection, in seconds. Use '0' to specify <i>no timeout</i> . (<i>Since 0.11</i>)	20
use_base_url_for_redirect	Optionally use <code>[trac] base_url</code> for redirects. In some configurations, usually involving running Trac behind a HTTP proxy, Trac can't automatically reconstruct the URL that is used to access it. You may need to use this option to force Trac to use the <code>base_url</code> setting also for redirects. This introduces the obvious limitation that this environment will only be usable when accessible from that URL, as redirects are frequently used. (<i>since 0.10.5</i>)	disabled
use_xsendfile	When true, send a <code>X-Sendfile</code> header and no content when sending files from the filesystem, so that the web server handles the content. This requires a web server that knows how to handle such a header, like Apache with <code>mod_xsendfile</code> or <code>lighttpd</code> . (<i>since 1.0</i>)	false
wiki_toolbars	Add a simple toolbar on top of Wiki <textarea>s. (<i>since 1.0.2</i>)	true

[tracwysiwyg]

templates	List of template names that the plugin will show a WYSIWYG editor on each <u>TracWiki</u> textarea. The plugin shows on all pages by default.	(no default)
wysiwyg_stylesheets	Add stylesheets to the WYSIWYG editor	(no default)

[translatedpages]

base_language	Base language to be used without prefix/suffix	En
languages_page	Page name of table containing available languages	TracLanguages
regexp	Regular expression to match a language code	([A-Z][a-z]{1,2}(:_[A-Z]{2})?)
template	Page name template of translated pages	{lang}:{page}

[versioncontrol]

allowed_repository_dir_prefixes	Comma-separated list of allowed prefixes for repository directories when adding and editing repositories in the repository admin panel. If the list is empty, all repository directories are allowed. (<i>since 0.12.1</i>)	(no default)
---------------------------------	---	--------------

[vote]

paths	List of URL paths to allow voting on. Globs are supported.	/ticket*, /wiki*
-------	--	------------------

[wiki]

ignore_missing_pages	Enable/disable highlighting <u>CamelCase</u> links to missing pages (<i>since 0.9</i>).	false
----------------------	---	-------

max_size	Maximum allowed wiki page size in characters. (<i>since 0.11.2</i>)	262144
render_unsafe_content	Enable/disable the use of unsafe HTML tags such as <code><script></code> or <code><embed></code> with the HTML WikiProcessor (<i>since 0.10.4</i>). For public sites where anonymous users can edit the wiki it is recommended to leave this option disabled (which is the default).	false
safe_schemes	List of URI schemes considered "safe", that will be rendered as external links even if <code>[wiki]</code> <code>render_unsafe_content</code> is false. (<i>since 0.11.8</i>)	cvs, file, ftp, git, irc, http, https, news, sftp, smb, ssh, svn, svn+ssh
split_page_names	Enable/disable splitting the WikiPageNames with space characters (<i>since 0.10</i>).	false

[wikiprint]

article_css_url	(no default)
book_css_url	(no default)
css_url	(no default)
extracontent_url	(no default)
frontpage_url	(no default)
httpauth_password	(no default)
httpauth_user	(no default)
omit_links	(no default)
omit_macros	(no default)
rebase_links	(no default)
toc_title	Table of Contents

Reference for special sections

1. [\[components\]](#)
2. [\[milestone-groups\]](#)
3. [\[repositories\]](#)
4. [\[svn:externals\]](#)
5. [\[ticket-custom\]](#)
6. [\[ticket-workflow\]](#)

[components]

This section is used to enable or disable components provided by plugins, as well as by Trac itself. The component to enable/disable is specified via the name of the option. Whether its enabled is determined by the option value; setting the value to `enabled` or `on` will enable the component, any other value (typically `disabled` or `off`) will disable the component.

The option name is either the fully qualified name of the components or the module/package prefix of the component. The former enables/disables a specific component, while the latter enables/disables any component in the specified package/module.

Consider the following configuration snippet:

[wiki]

```
[components]
trac.ticket.report.ReportModule = disabled
webadmin.* = enabled
```

The first option tells Trac to disable the report module. The second option instructs Trac to enable all components in the `webadmin` package. Note that the trailing wildcard is required for module/package matching.

See the *Plugins* page on *About Trac* to get the list of active components (requires `CONFIG_VIEW` permissions.)

See also: [TracPlugins](#)

[milestone-groups]

(since 0.11)

As the workflow for tickets is now configurable, there can be many ticket states, and simply displaying closed tickets vs. all the others is maybe not appropriate in all cases. This section enables one to easily create *groups* of states that will be shown in different colors in the milestone progress bar.

Example configuration (the default only has closed and active):

```
closed = closed
# sequence number in the progress bar
closed.order = 0
# optional extra param for the query (two additional columns: created and modified and sort on created)
closed.query_args = group=resolution,order=time,col=id,col=summary,col=owner,col=type,col=priority,col=
# indicates groups that count for overall completion
closed.overall_completion = truepercentage

new = new
new.order = 1
new.css_class = new
new.label = new

# one catch-all group is allowed
active = *
active.order = 2
# CSS class for this interval
active.css_class = open
# Displayed label for this group
active.label = in progress
```

The definition consists in a comma-separated list of accepted status. Also, '*' means any status and could be used to associate all remaining states to one catch-all group.

The CSS class can be one of: `new` (yellow), `open` (no color) or `closed` (green). New styles can easily be added using the following selector: `table.progress td.<class>`

[repositories]

(since 0.12 multirepos)

One of the alternatives for registering new repositories is to populate the `[repositories]` section of the `trac.ini`.

This is especially suited for setting up convenience aliases, short-lived repositories, or during the initial phases of an installation.

[components]

See [TracRepositoryAdmin](#) for details about the format adopted for this section and the rest of that page for the other alternatives.

[svn:externals]

(since 0.11)

The [TracBrowser](#) for Subversion can interpret the `svn:externals` property of folders. By default, it only turns the URLs into links as Trac can't browse remote repositories.

However, if you have another Trac instance (or an other repository browser like [ViewVC](#)) configured to browse the target repository, then you can instruct Trac which other repository browser to use for which external URL.

This mapping is done in the `[svn:externals]` section of the [TracIni](#)

Example:

```
[svn:externals]
1 = svn://server/repos1          http://trac/proj1/browser/$path?rev=$rev
2 = svn://server/repos2          http://trac/proj2/browser/$path?rev=$rev
3 = http://theirserver.org/svn/eng-soft  http://ourserver/viewvc/svn/$path/?pathrev=25914
4 = svn://anotherserver.com/tools_repository  http://ourserver/tracs/tools/browser/$path?rev=$rev
```

With the above, the `svn://anotherserver.com/tools_repository/tags/1.1/tools` external will be mapped to `http://ourserver/tracs/tools/browser/tags/1.1/tools?rev=` (and `rev` will be set to the appropriate revision number if the external additionally specifies a revision, see the [?SVN Book on externals](#) for more details).

Note that the number used as a key in the above section is purely used as a place holder, as the URLs themselves can't be used as a key due to various limitations in the configuration file parser.

Finally, the relative URLs introduced in [?Subversion 1.5](#) are not yet supported.

[ticket-custom]

In this section, you can define additional fields for tickets. See [TracTicketsCustomFields](#) for more details.

[ticket-workflow]

(since 0.11)

The workflow for tickets is controlled by plugins. By default, there's only a `ConfigurableTicketWorkflow` component in charge. That component allows the workflow to be configured via this section in the `trac.ini` file. See [TracWorkflow](#) for more details.

See also: [TracGuide](#), [TracAdmin](#), [TracEnvironment](#)