

Upgrade Instructions

Error: Macro TracGuideToc(None) failed

'NoneType' object has no attribute 'find'

Instructions

Typically, there are seven steps involved in upgrading to a newer version of Trac:

1. Update the Trac Code

Get the new version as described in [TracInstall](#), or your operating system specific procedure.

If you already have a 0.11 version of Trac installed via `easy_install`, it might be easiest to also use `easy_install` to upgrade your Trac installation:

```
# easy_install --upgrade Trac==0.12
```

If you do a manual (not operating system-specific) upgrade, you should also stop any running Trac servers before the installation. Doing "hot" upgrades is not advised, especially on Windows ([?#7265](#)).

You may also want to remove the pre-existing Trac code by deleting the `trac` directory from the Python `lib/site-packages` directory, or remove Trac `.egg` files from former versions. The location of the site-packages directory depends on the operating system and the location in which Python was installed. However, the following locations are typical:

- on Linux: `/usr/lib/python2.X/site-packages`
- on Windows: `C:\Python2.X\lib\site-packages`
- on MacOSX: `/Library/Python/2.X/site-packages`

You may also want to remove the Trac `cgi-bin`, `htdocs`, `templates` and `wiki-default` directories that are commonly found in a directory called `share/trac`. (The exact location depends on your platform.)

This cleanup is not mandatory, but makes it easier to troubleshoot issues later on, as you won't waste your time looking at code or templates from a previous release that are not being used anymore... As usual, make a backup before actually deleting things.

2. Upgrade the Trac Environment

Environment upgrades are not necessary for minor version releases unless otherwise noted.

After restarting, Trac should show the instances which need a manual upgrade via the automated upgrade scripts to ease the pain. These scripts are run via [trac-admin](#):

```
trac-admin /path/to/projenv upgrade
```

This command will do nothing if the environment is already up-to-date.

Note that a backup of your database will be performed automatically prior to the upgrade. This feature is relatively new for the PostgreSQL or MySQL database backends, so if it fails, you will have to backup the database manually. Then, to perform the actual upgrade, run:

```
trac-admin /path/to/projenv upgrade --no-backup
```

3. Update the Trac Documentation

Every [Trac environment](#) includes a copy of the Trac documentation for the installed version. As you probably want to keep the included documentation in sync with the installed version of Trac, [trac-admin](#) provides a command to upgrade the documentation:

```
trac-admin /path/to/projenv wiki upgrade
```

Note that this procedure will leave your WikiStart page intact.

4. Resynchronize the Trac Environment Against the Source Code Repository

Each [Trac environment](#) must be resynchronized against the source code repository in order to avoid errors such as "[?No changeset ??? in the repository](#)" while browsing the source through the Trac interface:

```
trac-admin /path/to/projenv repository resync '*'
```

5. Refresh static resources

If you have set up a web server to give out static resources directly (accessed using the `/chrome/` URL) then you will need to refresh them using the same command:

```
trac-admin /path/to/env deploy /deploy/path
```

this will extract static resources and CGI scripts (`trac.wsgi`, etc) from new Trac version and its plugins into `/deploy/path`.

Some web browsers cache CSS and Javascript files persistently, so you may need to instruct your users to manually erase the contents of their browser's cache.

6. Steps specific to a given Trac version

Upgrading from Trac 0.11 to Trac 0.12

Python 2.3 no longer supported

The minimum supported version of python is now 2.4

SQLite v3.x required

SQLite v2.x is no longer supported. If you still use a Trac database of this format, you'll need to convert it to SQLite v3.x first. See [?PySqlite#UpgradingSQLitefrom2.xto3.x](#) for details.

PySqlite 2 required

PySqlite 1.1.x is no longer supported. Please install 2.5.5 or later if possible (see [Trac database upgrade](#) below).

Multiple Repository Support

The latest version includes support for multiple repositories. If you plan to add more repositories to your Trac instance, please refer to [TracRepositoryAdmin#Migration](#).

This may be of interest to users with only one repository, since there's now a way to avoid the potentially costly resync check at every request.

Improved repository synchronization

In addition to supporting multiple repositories, there is now a more efficient method for synchronizing Trac and your repositories.

While you can keep the same synchronization as in 0.11 adding the post-commit hook as outlined in [TracRepositoryAdmin#Synchronization](#) and [TracRepositoryAdmin#ExplicitSync](#) will allow more efficient synchronization and is more or less required for multiple repositories.

Note that if you were using the `trac-post-commit-hook`, *you're strongly advised to upgrade it to the new hook* documented in the above references, as the old hook will not work with anything else than the default repository and even for this case, it won't trigger the appropriate notifications.

Authz permission checking

The authz permission checking has been migrated to a fine-grained permission policy. If you use authz permissions (aka `[trac] authz_file` and `authz_module_name`), you must add `AuthzSourcePolicy` in front of your permission policies in `[trac] permission_policies`. You must also remove `BROWSER_VIEW`, `CHANGESSET_VIEW`, `FILE_VIEW` and `LOG_VIEW` from your global permissions (with `trac-admin $ENV permission remove` or the "Permissions" admin panel).

Microsecond timestamps

All timestamps in database tables (except the `session` table) have been changed from "seconds since epoch" to "microseconds since epoch" values. This change should be transparent to most users, except for custom reports. If any of your reports use date/time columns in calculations (e.g. to pass them to `datetime()`), you must divide the values retrieved from the database by 1'000'000. Similarly, if a report provides a calculated value to be displayed as a date/time (i.e. with a column named "time", "datetime", "changetime", "date", "created" or "modified"), you must provide a microsecond timestamp, that is, multiply your previous calculation with 1'000'000.

Upgrading from Trac 0.10 to Trac 0.11

Site Templates and Styles

The templating engine has changed in 0.11 to Genshi, please look at [TracInterfaceCustomization](#) for more information.

If you are using custom CSS styles or modified templates in the `templates` directory of the [TracEnvironment](#), you will need to convert them to the Genshi way of doing things. To continue to use your style sheet, follow the instructions at [TracInterfaceCustomization#SiteAppearance](#).

Trac Macros, Plugins

The Trac macros will need to be adapted, as the old-style wiki-macros are not supported anymore (due to the drop of [?ClearSilver](#) and the HDF); they need to be converted to the new-style macros, see [WikiMacros](#). When they are converted to the new style, they need to be placed into the `plugins` directory instead and not `wiki-macros`, which is no longer scanned for macros or plugins.

For FCGI/WSGI/CGI users

For those who run Trac under the CGI environment, run this command in order to obtain the `trac.*gi` file:

```
trac-admin /path/to/env deploy /deploy/directory/path
```

This will create a `deploy` directory with the following two subdirectories: `cgi-bin` and `htdocs`. Then update your Apache configuration file `httpd.conf` with this new `trac.cgi` location and `htdocs` location.

Web Admin plugin integrated

If you had the `webadmin` plugin installed, you can uninstall it as it is part of the Trac code base since 0.11.

7. Restart the Web Server

If you are not running CGI, reload the new Trac code by restarting your web server.

Known Issues

parent dir

If you use a `trac` parent `env` configuration and one of the plugins in one child does not work, none of the children work.

Wiki Upgrade

`trac-admin` will not delete or remove default wiki pages that were present in a previous version but are no longer in the new version.

Trac database upgrade

A known issue in some versions of PySqlite (2.5.2-2.5.4) prevents the `trac-admin` upgrade script from successfully upgrading the database format. It is advised to use either a newer or older version of the `sqlite` python bindings to avoid this error. For more details see ticket [?#9434](#).

Upgrading Python

Upgrading Python to a newer version will require reinstallation of Python packages: Trac of course; also [?easy_install](#), if you've been using that. Assuming you're using Subversion, you'll also need to upgrade the Python bindings for `svn`.

Windows and Python 2.6

If you've been using CollabNet's Subversion package, you may need to uninstall that in favor of [?Algazam](#), which has the Python bindings readily available (see `TracSubversion`). The good news is, that works with no tweaking.

Changing Database Backend

SQLite to PostgreSQL

The [sqlite2pg](#) script on [trac-hacks.org](#) has been written to assist in migrating a SQLite database to a PostgreSQL database

Older Versions

For upgrades from versions older than Trac 0.10, refer first to [?wiki:0.10/TracUpgrade#SpecificVersions](#).

See also: [TracGuide](#), [TracInstall](#)