Error: Macro TranslatedPages(revision=7) failed

```
expected string or buffer
```

ARexx API

1. ADDRDELETE
2. ADDREDIT
3. ADDRFIND
4. ADDRGOTO
5. ADDRINFO
6. ADDRLOAD
7. ADDRNEW
8. ADDRRESOLVE
9. ADDRSAVE
10. APPBUSY
11. APPNOBUSY
12. FINDMAIL
13. FLUSHINDEXES
14. FOLDERINFO
15. GETCONFIGINFO
16. GETFOLDERINFO
17. GETMAILINFO
18. GETSELECTED
19. GETURL
20. HELP
21. HIDE
22. INFO
23. ISONLINE
24. LISTFREEZE
25. LISTSELECT
26. LISTUNFREEZE
27. MAILARCHIVE
28. MAILBOUNCE
29. MAILCHANGESUBJECT
30. MAILCHECK
31. MAILCOPY
32. MAILDELETE
33. MAILEDIT
34. MAILEXPORT
35. MAILFILTER
36. MAILFORWARD
37. MAILIMPORT
38. MAILINFO
39. MAILMOVE
40. MAILREAD
41. MAILREPLY
42. MAILSEND
43. MAILSENDALL
44. MAILSTATUS
45. MAILUPDATE
46. MAILWRITE

47. NEWMAILFILE
48. QUIT
49. READCLOSE
50. READINFO
51. READPRINT
52. READSAVE
53. REQUEST
54. REQUESTFILE
55. REQUESTFOLDER
56. REQUESTSTRING
57. RESTART
58. SCREENTOBACK
59. SCREENTOFRONT
60. SETFLAG
61. SETFOLDER
62. SETMAIL
63. SETMAILFILE
64. SHOW
65. USERINFO
66. WRITEATTACH
67. WRITEBCC
68. WRITECC
69. WRITEEDITOR
70. WRITEFROM
71. WRITEIDENTITY
72. WRITELETTER
73. WRITEMAILTO
74. WRITEOPTIONS
75. WRITEQUEUE
76. WRITEREPLYTO
77. WRITESEND
78. WRITESUBJECT
79. WRITETO

WRITEQUEUE

NOMBRE

WriteQueue -- Colocar el nuevo mensaje en la cola de mensajes salientes.

PLANTILLA

HOLD/S

FUNCIÓN

Sitúa el mensaje recién escrito en la cola de mensajes salientes.

ENTRADAS

`HOLD/S` - marcar el mensaje como "retenido" para evitar que se envíe por error (V2.0)

RESULTADOS

RC se pone a 10 si no se ha designado previamente una ventana de escritura como "activa" por medio de MAILWRITE ?.

NOTAS

EJEMPLO

```
/* Escribir un nuevo mensaje */

         MAILWRITE\\
         WRITETO jefe@example.com\\
         'WRITESUBJECT "No creo que pueda ir hoy a trabajar"'\\
         WRITELETTER 'work:excusas.txt'\\
         WRITEQUEUE\\
```

FALLOS

VÉASE TAMBIÉN

MAILWRITE ?, WRITESEND ?